COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department and author as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence, prepared by Jacobs". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

This log has been contributed to the Queensland Geotechnical Database with the permission of Jacobs.

S	K	Ņ	1

SOIL LOG

HOLE NO: AHBV 19

PROJECT : Brisbane Valley Grade Separation JOB NO : QB10200.4 PAGE : 1 OF 1														
			: 471398, N: 6949525 (56 MGA94) SURFACE ELEVATION : 46.7 (AHD)								LOCATION : Brisbane Valley Hwy			
RIG TYP	PE :	Nis	san F	Rig						CONTRACTOR : R. Battison	BUCKET WIDTH : 0.1m			
DATE DRILLED : 1/6/11 to 1/6/11 LOGGED BY : LN CHECKED BY : VP STANDARD : AS1736														
DRILLING & WATER DETAIL	Moisture Content	Dry Density	% Fines	Atterberg Limits	SAMPLES & FIELD DATA	RL (m)	DEPTH (m)	GRAPHIC LOG	U. S. C.	MATERIAL DESCRIPTION Soil Type, Colour, Plasticity or Particle Characteristic Secondary and Minor Components	MOISTURE	CONSISTENCY/DENSITY	5 10 (blows/100mm) 20	
							-		SM	0.65AND- silty SAND, fine to medium sand, dark brown, some clay, trace \fine gravel, 10% organic, moist, loose CLAY - sandy CLAY, low to medium plasticity, light grey with red mottling, fine to medium sand, moist, firm 0.40m	M	F		0.00: FILL 0.05: FILL
					0.65m	46.2	-0.5		сн	CLAY - silty CLAY, high plasticity, dark grey to black, trace fine sand, trace fine gravel, moist, stiff	м	St		0.40: FILL -
					0.85m 07/046 1 \2		-		сн	0.65m CLAY - sandy CLAY, high plasticity, dark grey to black, fine to coarse sand, moist, stiff	м	St		0.65: NATURAL PP @ 0.7m = 190 kPa
					0.390m	45.7	- - - - - - - - - - - - - - - - - - -		сн	CLAY - sandy CLAY, high plasticity, grey orange mottled, fine to medium sand, moist, very stiff 1.60m CLAY - sandy CLAY, high plasticity, light orange grey, some gravel, moist, very stiff	м	VSt		
						44.7			сн	1.90m CLAY - gravelly sandy CLAY, high plasticity, light orange grey, some fine gravel, moist, very stiff	м м	VSt		
						44.2			сн	2.20m CLAY - silty, sandy CLAY, high plasticity, light yellow orange, fine to medium sand, moist, very stiff 2.50m	м	VSt		
							-		SM	SAND - silty SAND, fine to coarse sand, trace to minor fine gravel, orange brown, moist, dense.	м	D		
						43.7				Terminated @ 3.0 m. No water encountered.				
AS AU WB W RR RC	z = V Z = V	uger ore olling OUNI Vater Vater	level level	HQ NQ PQ NML(TER S) (static) (during	HQ Co NQ Co PQ Co C NMLC (MBOLS (drilling) g drilling	ring fing Cori	ing	ES E EW E	nv So nv Wa	SAMPLES & FIELD TESTS DCP- N (Blows isturbed Sample U Undisturbed Tube Sample VS Very Soft its Sample W Water Sample S Soft urbed Sample W Water Sample F Firm MOISTURE CONDITION St Stiff DE = Dry M = Moist W = Wet	0 - 1 1 - 2 2 - 3 3 - 7 7 - 1	3	VS S F St VSt	NSISTENCY (Su) {N-value} Very Soft 12 kPa {0-2} Soft 12 - 25 {2-4} Firm 25 - 50 {4-8} Stiff 50 - 100 {8-15} Very Stiff 100 - 200 {15-30} Hard > 200 kPa {>30}

(c) State of Queensland (Department of Transport and Main Roads) 2020, CC BY 4.0. Please note copyright and limitation of liability notices on attached cover page.