

## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>



**Queensland  
Government**

**GEOTECHNICAL  
BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No **BH12**

Sheet 1 of 3

REFERENCE No **H12908**

PROJECT	Boyne River Bridge Repalcement		
LOCATION	Pier 5, RHS	COORDINATES 323425.4 E; 7159863.7 N	
PROJECT No	FG6482	SURFACE RL 116.02m	PLUNGE 90°
			DATE STARTED 07/07/2017
			GRID DATUM MGA Z56
JOB No	249/435/375550	HEIGHT DATUM AHD	BEARING °
			DATE COMPLETED 09/07/2017
			DRILLER NorthCoast Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASHBORING CORE DRILLING	RQD (%) CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USCS WEATHERING	INTACT STRENGTH	DEFECT SPACING	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
1				A	Silty SAND (Alluvium) Brown, moist, loose. Fine to medium grained sand. Trace gravel. Zones of Sandy CLAY <50mm thick.	(SM)					1, 3, 5 N=8 SPT
2	114.02			B	Gravelly SAND (Alluvium) Grey brown, moist, very loose to loose. Medium to coarse grained sand. Fine to medium grained gravel, sub rounded. Trace Silt.	(SP)				2.20m: Cobbles ~60mm	1, 2, 2 N=4 SPT
3				C	3.00m: Becoming medium dense.						6, 7, 9 N=16 SPT
4	112.02			D	Sandy GRAVEL (Alluvium) Grey brown, wet, medium dense. Medium to coarse grained sand. Fine to medium grained gravel, sub rounded <20mm. Trace Cobbles <~80mm.					4.20m: Cobbles ~80mm	10, 11, 5 N=16 SPT
5				E						5.20m: Cobbles ~80mm	8, 9, 6 N=15 SPT
6				F							5, 7, 5 N=12 SPT
7				G		(GP)					6, 11, 9 N=20 SPT
8				H							7, 16, 13 N=29 SPT
9				I	9.00m: Becoming Sandy GRAVEL with Clay						7, 10, 14 N=24 SPT
	106.02										

Continued on next sheet

REMARKS: Je1 - Evergreen Formation.

<b>LOGGED BY</b>	<b>REVIEWED BY</b>
J. Armstrong	S. Foley



**Queensland  
Government**

**GEOTECHNICAL  
BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No **BH12**

Sheet 2 of 3

REFERENCE No **H12908**

PROJECT	Boyne River Bridge Repalcement		
LOCATION	Pier 5, RHS	COORDINATES 323425.4 E; 7159863.7 N	
PROJECT No	FG6482	SURFACE RL 116.02m	PLUNGE 90°
			DATE STARTED 07/07/2017
			GRID DATUM MGA Z56
JOB No	249/435/375550	HEIGHT DATUM AHD	BEARING °
			DATE COMPLETED 09/07/2017
			DRILLER NorthCoast Drilling

DEPTH (m)	R.L. (m)	FAUGER CASING WASHBORING CORE DRILLING	RQD (%) CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USCS WEATHERING	INTACT STRENGTH	DEFECT SPACING	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS		
												EH	VH
105.82				J	Sandy GRAVEL (Alluvium) Cont'd.	(SM)				18, 30/110mm hb	SPT		
111.052					Clayey SAND (Alluvium) Pale grey, moist, very dense. Fine to medium grained sand.	(SC)							
12.00				K	Silty CLAY with Sand (Alluvium) Pale brown, wet, very stiff. Medium plasticity. Fine grained sand.					9, 10, 12 N=22	SPT		
12.00				L	12.0m: Becoming hard.					8, 30/120mm	SPT		
13.00				M	13.00m: Sandy CLAY, hard.	(CI)				12, 17, 26 N=43	SPT		
14.00				N	14.00m: Silty CLAY with Sand.					10, 23, 30/110mm	SPT		
15.00				O						12, 30/140mm	SPT		
100.52				P	SANDSTONE (Je1) XW: Recovered as Clayey SAND. Pale grey to brown, moist, very dense. Fine to medium grained sand.					30/130mm	SPT		
17.00				O		XW				30/80mm	SPT		
18.00				R	18.00m: Recovered as Clayey SAND with Gravel. Fine to medium grained gravel, angular.					30/50mm hb	SPT		
97.02				S	SANDSTONE (Je1) MW: Pale grey and brown, fine grained, medium bedded, low to medium strength.					30/50mm hb	SPT		
96.02			(27)			HW MW							

Continued on next sheet

REMARKS: Je1 - Evergreen Formation.

<b>LOGGED BY</b>	<b>REVIEWED BY</b>
J. Armstrong	S. Foley



**GEOTECHNICAL  
BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	<b>BH12</b>
Sheet 3 of 3	
REFERENCE No	<b>H12908</b>

PROJECT	Boyne River Bridge Repalcement		
LOCATION	Pier 5, RHS	COORDINATES	323425.4 E; 7159863.7 N
PROJECT No	FG6482	SURFACE RL	116.02m
		PLUNGE	90°
		DATE STARTED	07/07/2017
		GRID DATUM	MGA Z56
JOB No	249/435/375550	HEIGHT DATUM	AHD
		BEARING	°
		DATE COMPLETED	09/07/2017
		DRILLER	NorthCoast Drilling

DEPTH (m)	R.L. (m)	FAUGER CASING WASHBORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USCS WEATHERING	INTACT STRENGTH		DEFECT SPACING								ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS																
									EH	VH	H	M	J	VL	EU	EC	VC	C			M	W	VW	EW												
21	90.52		100 (21)			SANDSTONE (Je1) MW: Cont'd. - BP: 20° to 40° (2-3/m); Pl-Un/Ro; Tl; Fe St; Cly Vr - Js: 0° to 30° (1-2/m); Pl-Un/Ro; TI-OP; Fe St; Cly Vr - Js: 30° to 60° (2-3/m); Pl-Un/Ro; TI-CD; Fe St; Cly Vr; Ct <50mm		MW	H														Is(50)=1.60 MPa	D (20.10m)												
26	87.67		50 (13)			SANDSTONE (Je1) HW: Brown to grey, fine grained, medium bedded, very low to low strength. Bedding is indistinct. Brecciated zones throughout. - BP: 40° to 50° (<1/m); Pl/Ro; TI; Cly Vr - Js: 0° to 20° (8-10/m); Pl-Un/Ro; TI-OP; Cly Vr - Js: 70° to 90° (2-3/m); Un/Ro; TI-CD; Cly Vr		HW	LM																											
29	86.22		78 (61)			SANDSTONE (Je1) SW: Pale grey, medium to coarse grained, medium bedded, medium to high strength. - BP: 5° to 15° (3-4/m); Pl-Un/Ro; TI; some Fe St From 27.0m: MW zone, medium to high strength.		MW	MH																											

Borehole completed at 29.80m


REMARKS: Je1 - Evergreen Formation.

<b>LOGGED BY</b>	<b>REVIEWED BY</b>
J. Armstrong	S. Foley

**CORE PHOTO LOG**  
 DEPARTMENT OF TRANSPORT AND MAIN ROADS  
 GEOTECHNICAL SECTION




Project Name	<b>Boyne River Bridge Replacement</b>		
Project No.	FG6482	Date	09/07/2017
Borehole No.	BH12	Reference No.	H12908
Location	Pier 5, RHS	Start Depth (m)	19.05
Submitted By	S. Louei	Finish Depth (m)	29.80
Remarks			



**CORE PHOTO LOG**  
 DEPARTMENT OF TRANSPORT AND MAIN ROADS  
 GEOTECHNICAL SECTION



Project Name	<b>Boyne River Bridge Replacement</b>		
Project No.	FG6482	Date	09/07/2017
Borehole No.	BH12	Reference No.	H12908
Location	Pier 5, RHS	Start Depth (m)	19.05
Submitted By	S. Louei	Finish Depth (m)	29.80
Remarks			



SCALE (mm)