

## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>



ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No BH116
SHEET 1 of 3
REFERENCE No 12062

PROJECT Mackay Ring Road Geotechnical Investigation - Stage 1
LOCATION Peak Downs Hwy Overpass Abutment A; CH: 5572m; COORDINATES 720979.2 E; 7657925.1 N
PROJECT No FG6184 SURFACE R.L. 12.46m PLUNGE DATE STARTED 30/9/14 GRID DATUM GDA 94 /MGA Zone 56
JOB No HEIGHT DATUM AHD BEARING DATE COMPLETED 1/10/14 DRILLER Saxon Drilling

Table with columns: DEPTH (m), R.L. (m), AUGER CASING WASH BORING CORE DRILLING, CORE REC %, RQD (%), SAMPLE, MATERIAL DESCRIPTION, LITHOLOGY, USC WEATHERING, INTACT STRENGTH, DEFECT SPACING (mm), GRAPHIC LOG, ADDITIONAL DATA AND TEST RESULTS, SAMPLES TESTS. Includes soil descriptions like Clayey SILT, Silty CLAY, Clayey SAND, and Sandy CLAY.

REMARKS # Sample failed along existing defect surface.

LOGGED BY MS

**ENGINEERING  
BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No   BH116  

SHEET   2   of   3  

REFERENCE No   12062  

PROJECT   Mackay Ring Road Geotechnical Investigation - Stage 1    
 LOCATION   Peak Downs Hwy Overpass Abutment A; CH: 5572m;   COORDINATES   720979.2 E; 7657925.1 N    
 PROJECT No   FG6184   SURFACE R.L.   12.46m   PLUNGE            DATE STARTED   30/9/14   GRID DATUM   GDA 94 /MGA Zone 55    
 JOB No            HEIGHT DATUM   AHD   BEARING            DATE COMPLETED   1/10/14   DRILLER   Saxon Drilling  

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	INTACT STRENGTH											DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS						
							USC	WEATHERING		STRENGTH		STRENGTH		STRENGTH		STRENGTH						STRENGTH		STRENGTH			
10	2.46						EH	VH	H	M	J	VL	EL	EC	VC	W	WW	WV	EW								
10	2.46			K	<b>Silty CLAY (ALLUVIUM)</b> (Cont'd) Becoming mainly grey, yellow and pale brown.	(CH)																4.5,7 N=12	SPT				
11				L		(CH)																6.9,11 N=20	SPT				
12				M	12.00m: Trace fine grained sand.	(CH)																6.11,12 N=23	SPT				
12.60	-0.14				<b>Clayey SAND (ALLUVIUM)</b> Yellow-brown, moist to dry, dense. Mainly fine to medium grained.	(SC)																10,11,23 N=34	SPT				
13				N		(SC)																					
14	-1.74			P	<b>Silty CLAY (RESIDUAL)</b> Pale brown, orange mottled grey, moist, very stiff. High plasticity.	(CH)																8,10,13 N=23	SPT				
15				Q		(CH)																11,10,13 N=23	SPT				
16				R		(CH)																6,10,13 N=23	SPT				
17				S	17.00m: Becoming hard.	(CH)																9,15,19 N=34	SPT				
18				T	18.00m: Becoming very stiff.	(CH)																8,14,15 N=29	SPT				
19				U	19.00m: Colour change to pale grey. Trace fine grained sand.	(CH)																6,8,10 N=18	SPT				
20	-7.54					(CH)																					

TMIR JAN 15.GLB Log\_A\_ENG ENGINEERING BOREHOLE LOG W LITHOLOGY FG6184 - BOREHOLES.GPJ <<DrawingFile>> Dataget CPT Tool gInt Add-In 04/09/2015 10:50

REMARKS # Sample failed along existing defect surface.

LOGGED BY  
MS



**Queensland  
Government**

# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No   BH116    
SHEET   3   of   3    
REFERENCE No   12062  

PROJECT   Mackay Ring Road Geotechnical Investigation - Stage 1    
LOCATION   Peak Downs Hwy Overpass Abutment A; CH: 5572m;   COORDINATES   720979.2 E; 7657925.1 N    
PROJECT No   FG6184   SURFACE R.L.   12.46m   PLUNGE            DATE STARTED   30/9/14   GRID DATUM   GDA 94 /MGA Zone 55    
JOB No            HEIGHT DATUM   AHD   BEARING            DATE COMPLETED   1/10/14   DRILLER   Saxon Drilling  

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
20	-7.54				V	<b>Clayey SAND (RESIDUAL)</b> Pale grey, moist to dry, medium dense. Fine to medium grained.	(SC)					8,11,13 N=24	SPT
21.00	-8.54				W	<b>Sandy CLAY (RESIDUAL)</b> Pale grey, moist, very stiff. Low plasticity. Fine grained sand.	(CL)					6,13,15 N=28	SPT
22.00	-9.54				X	<b>GRANODIORITE (Kgwu)</b> XW: Recovered as brown-grey, dry, very dense Clayey SAND. Fine to medium grained.	XW					19,30/130	SPT
23	-10.74					<b>GRANODIORITE</b> MW: Pale grey, brown, medium grained, massive, low to medium strength. Some XW zones, EL strength. Highly fractured in parts. Defects: - Js: 30° (2/m); PI/Ro, OP, Cly Vr; - Js: 50°-60° (4/m); PI/Ro, OP, Cly Vr; - Js: 70°-80° (3/m); PI/Ro, OP, Cly Vr;	MW				Is(50) = 0.35MPa Is(50) = 0.21MPa	A (23.25m) D (23.30m)	
24			(40)				XW				23.59m-23.65m: XW zone, EL strength.		
			100				MW				23.80m-23.93m: XW zone, EL strength.		
			(13)				XW				24.10m-24.18m: XW zone, EL strength.		
							MW				24.83m-24.93m: XW zone, EL strength.		
25			100				XW					Is(50) = 0.19MPa	D (25.44m)
			(13)				MW						
26							XW				26.20m-26.28m: XW zone, EL strength.	Is(50) = 0.06MPa; # Is(50) = 0.15MPa	D (26.05m) A (26.10m)
			100			26.28m: Becoming medium to high strength.	MW						
			(7)				MW					Is(50) = 0.73MPa; # Is(50) = 1.02MPa	D (27.23m) A (27.28m)
27													
			100										
			(18)										
28	-15.89					<b>MICRODIORITE (Kgwu)</b> SW: Grey-black, fine to medium grained, massive, very high strength. Highly fractured. Defects: - Js: 40° (2/m); PI/Ro, OP, Fe St; - Js: 50° (5/m); PI/Ro, OP, Fe St; - Js: 70°-80° (6/m); PI/Ro, OP, Fe St;	SW					Is(50) = 3.38MPa Is(50) = 3.78MPa	A (28.63m) D (28.80m)
29	-16.74					Borehole terminated at 29.2m.							
30													

REMARKS # Sample failed along existing defect surface.

LOGGED BY  
MS


**CORE PHOTO LOG**

DEPARTMENT OF TRANSPORT & MAIN ROADS  
 Geotechnical Branch  
 35 Butterfield Street, HERSTON Qld 4006  
 Phone 07 3066 3336



Department of  
 Transport and Main Roads

Project Name	<b>Mackay – Ring Road</b>		
Project No	FG6184	Date	01/10/14
Borehole No	BH 116	TMR H No	12062
Location	Peak Downs Hwy Overpass	Start Depth (m)	23.2
Detail	Abutment A	Finish Depth (m)	29.2
Chainage	<b>5572</b>	Submitted By	J. Lopez
Remarks			



SCALE 1:5