

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH111
SHEET 1 of 4
REFERENCE No H10895

PROJECT Ipswich Motorway Upgrade - Rocklea to Darra
LOCATION Oxley Creek Overflow COORDINATES 498781.2 E; 6951053.7 N
PROJECT No FG5779 SURFACE R.L. 2.38m PLUNGE -90° DATE STARTED 02/11/10 GRID DATUM GDA94
JOB No 140/U16/902 HEIGHT DATUM AHD BEARING DATE COMPLETED 03/11/10 DRILLER R&D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	2.38											
0.13					A	Silty CLAY Brown to grey, moist, firm stiff Medium plasticity. Becoming grey with depth.	(CH)				Based on drillers logs only inferred GWT	2,3,4 N=7 SPT
0.13					B	Sandy CLAY (Alluvium) Grey to brown, moist, firm to very stiff . Low to medium plasticity.					p'c=96kPa OCR=2.9	U100
					C	Sand fraction fine grained; clayey sand below 4m depth. Sand fraction decreasing with depth.						RW,1,3 N=4 SPT
					D		(CI/ML)					4,4,3 N=7 SPT
					E							RW,2,4 N=6 SPT
	-3.62				F	Silty SAND (Residual) Brown to grey, moist, very loose to mainly medium dense . Sand fraction fine grained; occasional silty clay layers in parts.						4,6,13 N=19 SPT
					G							9,9,9 N=18 SPT
					H		(SM)					7,8,8 N=16 SPT
	-7.02				J	Becoming very soft silty clay below 9.0m app. 400mm thick.						1,2,0 N=2 SPT
10						(See over)					▽ 11/2/2011 ▽ 4/2/2011	

REMARKS Observation well installed, infiltration zone from 6.3m to 35.0m.

LOGGED BY
BW / SG

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH111
SHEET 2 of 4
REFERENCE No H10895

PROJECT Ipswich Motorway Upgrade - Rocklea to Darra
LOCATION Oxley Creek Overflow COORDINATES 498781.2 E; 6951053.7 N
PROJECT No FG5779 SURFACE R.L. 2.38m PLUNGE -90° DATE STARTED 02/11/10 GRID DATUM GDA94
JOB No 140/U16/902 HEIGHT DATUM AHD BEARING DATE COMPLETED 03/11/10 DRILLER R&D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH						DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
								EH	VH	H	M	L	VL				
10	-7.62				K	Silty SAND (Residual) Cont'd	(SM)									4,7,5 N=12	SPT
11	-8.82				L	Silty CLAY (Residual) Grey, moist, firm. stiff High plasticity; minor traces of organic material.	(CH)									1,2,5 N=7	SPT
12	-9.62				M	SILTSTONE FINE GRAINED SEDIMENTARY ROCK COMPRISED MAINLY OF SILT SIZED PARTICLES. XW:Generally exhibits engineering properties of pale brown to grey, moist, very stiff to hard clayey silt.										5,9,13 N=22	SPT
13					N	High plasticity. Traces of organic material.	XW									8,11,16 N=27	SPT
14					P											9,15,23 N=38	SPT
15	-12.62				Q	HW: Generally exhibits engineering properties of pale grey to brown, moist, hard, clayey silt. Low plasticity. Occasional fine grained HW sandstone bands.										19,25,30/140mm N>50	SPT
16					R											11,20,27 N=47	SPT
17					S		HW									12,22,29 N>50	SPT
18					T											18,20,27 N=47	SPT
19	-16.62				U	CLAYSTONE FINE GRAINED SEDIMENTARY ROCK COMPRISED MAINLY OF CLAY SIZED PARTICLES.	HW									DD = 1.76t/m ³ ; WD = 2.09t/m ³ ; MC = 18.8%; UCS=1222KPa 14,20,23 N=43	SPT
20						(See over)										DD = 1.76t/m ³ ; WD = 2.10t/m ³ ;	

REMARKS Observation well installed, infiltration zone from 6.3m to 35.0m.

LOGGED BY
BW / SG

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH111
SHEET 3 of 4
REFERENCE No H10895

PROJECT Ipswich Motorway Upgrade - Rocklea to Darra
LOCATION Oxley Creek Overflow COORDINATES 498781.2 E; 6951053.7 N
PROJECT No FG5779 SURFACE R.L. 2.38m PLUNGE -90° DATE STARTED 02/11/10 GRID DATUM GDA94
JOB No 140/U16/902 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 03/11/10 DRILLER R&D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH					DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
								EH	VH	H	M	J				
20	-17.62					CLAYSTONE (Cont'd) HW: Brown, bedded with minor lamination, fine grained, mainly very low strength. Generally defects are rare -Drilling induced bedding/lamination partings @ 5-10° (1/m) Defects are close to wide spaced, planar, smooth, tight, clean. Occasional fine grained sand in parts.	HW								MC = 19.4%; UCS=873KPa Mudstone interbeds app. 400mm thick. Is(50) = 0.07MPa	o
21			(86)												Is(50) = 0.07MPa	o
22			100	(98)											Is(50) = 0.07MPa Is(50) = 0.06MPa DD = 1.90t/m ³ ; WD = 2.20t/m ³ ; MC = 16%; UCS=804KPa	x o
23			100	(100)											Is(50) = 0.06MPa Is(50) = 0.04MPa	x o
24			100	(92)											Is(50) = 0.09MPa Is(50) = 0.09MPa DD = 1.81t/m ³ ; WD = 2.12t/m ³ ; MC = 16.8%; UCS=2300KPa	x o
25	-22.69					Interbedded SANDSTONE and MUDSTONE HW: Grey to dark grey, fine grained, bedded, very low strength. Sand particles are fine grained; dark grey mudstone interbeds are generally >50mm thick. Defects: - Bedding / lamination parting @ 10° (3/m) - Joint @ 10° (3/m) Defects are close to medium spaced, planar, smooth, tight and clean.	HW								∇ 22/12/2010 Is(50) = 0.02MPa	o
26			100	(50)											Is(50) = 0.06MPa Is(50) = 0.10MPa	x o
27						MUDSTONE MW: Dark grey, fine grained, laminated, mainly very low to low strength. Defects: - Lamination parting @ 10° (1-2/m) - Joint @ 40° (<1/m) Defects are close to medium spaced, planar, smooth, tight and clean.	MW								Is(50) = 0.14MPa Is(50) = 0.24MPa Is(50) = 0.09MPa Is(50) = 0.07MPa	x o x o
28			100	(77)											Is(50) = 0.08MPa Is(50) = 0.06MPa	x o
29			100	(72)												
30	-25.02					(See over)										

REMARKS Observation well installed, infiltration zone from 6.3m to 35.0m.

LOGGED BY
BW / SG



ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No	<u>BH111</u>
SHEET	<u>4</u> of <u>4</u>
REFERENCE No	<u>H10895</u>


PROJECT Ipswich Motorway Upgrade - Rocklea to Darra
LOCATION Oxley Creek Overflow COORDINATES 498781.2 E; 6951053.7 N
PROJECT No FG5779 SURFACE R.L. 2.38m PLUNGE -90° DATE STARTED 02/11/10 GRID DATUM GDA94
JOB No 140/U16/902 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 03/11/10 DRILLER R&D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%) CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH							DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
							EH	VH	H	M	J	L	VL				
30	-27.62				MUDSTONE MW: (Cont'd) Occasional high strength bands below @31m depth.	MW								20	DD = 1.74t/m ³ ; WD = 2.08t/m ³ ; MC = 19.2%; UCS=1305KPa Jt @ 40 Is(50) = 0.08MPa Is(50) = 0.08MPa Is(50) = 3.14MPa Is(50) = 8.03MPa Is(50) = 3.74MPa Is(50) = 1.25MPa DD = 1.68t/m ³ ; WD = 2.04t/m ³ ; MC = 21.6%; UCS=1589KPa Is(50) = 0.06MPa Is(50) = 0.09MPa DD = 1.65t/m ³ ; WD = 2.02t/m ³ ; MC = 22.6%; UCS=2074KPa Piezometer tip @ 30.0m depth Is(50) = 0.08MPa Is(50) = 0.10MPa DD = 1.58t/m ³ ; WD = 1.97t/m ³ ; MC = 24.8%; UCS=1891KPa Is(50) = 0.08MPa Is(50) = 0.09MPa Is(50) = 0.05MPa Is(50) = 0.11MPa Is(50) = 0.08MPa Is(50) = 0.15MPa DD = 1.62t/m ³ ; WD = 2.02t/m ³ ; MC = 24.2%; UCS=1606KPa DD = 1.78t/m ³ ; WD = 2.10t/m ³ ; MC = 18%; UCS=799KPa		
31			100 (70)														
32			100 (98)														
33			100 (93)														
34			100 (100)														
35	-32.62		100														
36																	
37																	
38																	
39																	
40																	

REMARKS Observation well installed, infiltration zone from 6.3m to 35.0m.

LOGGED BY BW / SG


Project: **Ipswich Motorway Upgrade - Rocklea to Darra**
Borehole No: **BH 111**
Start Depth: 20.00m
Finish Depth: 35.00m
Project No: FG5779
H No: H10895



SCALE 1:5

F:GEO043/1

Project: **Ipswich Motorway Upgrade - Rocklea to Darra**
Borehole No: **BH 111**
Start Depth: 20.00m
Finish Depth: 35.00m
Project No: FG5779
H No: H10895



SCALE 1:5

F:GEO043/1