## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department and author as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence, prepared by Arup". This licence does not apply to the Queensland Government logo or trademarks.

## LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

This log has been contributed to the Queensland Geotechnical Database with the permission of Arup.

ARI CLIENT				<b>D</b> (	DREHOLE RECORD	BH321 HOLE			OF 3		
PROJECT		IPSWICH MOTORWAY UPGRADE - WACOL TO DARRA  CHECK DRILLE								ay-08 to 15-May-08	
CONTRACTOR DRILL MODEL DRILLER	En	rratest dson 3000 rratest	)		ANGLE Vertical BEARING - HOLE DIAMETER 100mm ()	GROUND LEVEL RL: LOCATION 327			L 27 2759 ustral	27.77m 759 E 150435 N tralian Height Datum	
DRILLING STRATA					MATERIAL DESCRIPTION	CONDITION				OBSERVATIC	
SAMPLE, TEST, BIT, SUPPORT, ETC.	R.L.	R.L. DEPTH		LEGEND	SOIL TYPE Plasticity / Grain Size, Colour, Minor Components	WATER / MOISTURE	COHESIVI	COHES	SIVE	SOIL ORIGIN, STRUCTURE, ETC.	
	m	m	GROUP		ASPHALT.	D	S T S	±      ¥   §	<u>~</u> }	FILL	
	27.57	0.20			GRAVEL, angular, Roadbase.	D -	_			FILL	
	27.17	0.60			SAND and GRAVEL sand fine to coarse, gravel medium grained - angular black.	D	-			FILL	
		1 1.00 +	SM		Silty SAND (SM) medium dense, fine to medium grained, black, with gravel fine grained subangular, mixed with clayey sand and sand.	D -	_			FILL	
SPTLS N=12 7;8,4	1	<b>2</b> 2.00	CI		- Gravelly CLAY (CI) stiff, light orange-brown, gravels medium grained - subangular, with sand.	- - D				COHES	
	24.97	- - - 2.80	CI		Sandy CLAY (CI) stiff, grey-brown mottled orange, sand medium	- - M				COHES	
PTLS N=11 1;7,4		+3			grained,.	- - -					
N. 46		† <b>+ 4</b> +			-	- - -					
SPTLS N=10 3;2,8		+ + +5			· -						
	22.27	5.50	SM	× · · ×	- Silty SAND (SM) very dense, medium grained, black brown, poorly graded.	_ D				NONCO	
PTLS N=60** 30/150s		+6 +		×		-					
	20.97	- 6.80 - 7		× · · · ·	Clayey SANDSTONE, medium to coarse grained, very low strength, – extermely weathered, red-brown, heavy ironstaining, with ironstone,.	D -				SNDSTN	
PTLS N=37 13;19,18		+ + 8 +			-	- - -					
	19.37	8.40	CI CH		Silty Sandy CLAY (CI-CH) very stiff, yellow-brown, sand fine grained,.	D				COHES	
	18.97	9 8.80 - 9			Silty MUDSTONE, extremely low strength, extremely weathered, – yellow-brown, heavy ironstaining, high silt content, with gravel fine grained angular, properties of Silty CLAY (CI) very stiff.	_ M-W				MUD	
		<u> </u>						ЩШ			

ARL	<b>/</b> 1				HOLE	OF	3	
CLIENT	DMR	CH MOTO		GRADE - WACOL TO DARRA	LOGGED BY CHECKED BY	MAJ GWB	GWB	
CONTRACTOR		rratest	RWATUFO	ANGLE Vertical	DRILLED DATE  GROUND LEVEL	13-May-08 to 15-Ma L RL 27.77m		
DRILL MODEL DRILLER	Endson 3000 Terratest			BEARING - HOLE DIAMETER 100mm ()	LOCATION  ELEVATION DATUM	32759 E 150435		
	1			· · · · · · · · · · · · · · · · · · ·	COORDINATE SYSTEM	ū	iii Dalu	
DRILLING		STRAT	A	MATERIAL DESCRIPTION	CONDITION	OB	SERV	
SAMPLE, TEST,			MBOL		CONSISTENC		OIL OF	
BIT, SUPPORT, ETC.	R.L.	DEPTH	GROUP SYMBOL	SOIL TYPE Plasticity / Grain Size, Colour, Minor Components			TRUCT	
LIO.	m	m	GROU		M N N N N N N N N N N N N N N N N N N N			
-				Silty MUDSTONE, extremely low strength, extremely weathered, - yellow-brown, heavy ironstaining, high silt content, with gravel fine grained angular, properties of Silty CLAY (CI) very stiff. (continued)	-		MU	
-		<u> </u>		grained drigatal, proportice of early early (er) very earlie (continued)				
-		+		•	-			
SPTLS N=33 8;14,19	-	+11 +		<del>-</del>				
-		<u> </u>						
-					-			
-	-	12		12.00m - 16.00m high plasticity	-			
-					-			
- -		‡		•				
-	-	13		13.00m with pockets of Clayey Siltstone	-			
		Į						
<del>.</del>		<u> </u>						
SPTLS N=29		14			1 w			
7;13,16		‡						
-		†			-			
- -		- - 15		-				
		<u>†</u>						
-		Ţ						
- -	11.77 -	<b>16</b> 16.00						
-		+ 10.00		Silty MUDSTONE, very low strength, extremely weathered, dark - grey-brown heavy ironstaining, properties of Silty CLAY (CH) hard, lenses of sandy ironstone.	D-M		MU	
• -		‡		•				
-		<u> </u>						
SPTLS N=40 11;15,25		+ 17 +						
- -		<u> </u>						
-		+			-			
<del>-</del> -	-	+ 18 +		-				
-		†						
-		Į						
<del>-</del> -	-	19			-			
-		+			-			
-		‡						
-								

ARU	JP	)		В	DREHOLE RECORD		3H32	21	SHEET 3 OF 3
CLIENT PROJECT	DMR IPSWIC	СН МОТО	DRW/	AY UPG	GRADE - WACOL TO DARRA	CH	GGED BY ECKED BY ILLED DATE	MAJ GWB	y-08 to 15-May-08
CONTRACTOR DRILL MODEL DRILLER	End	ratest dson 3000 ratest	)		ANGLE Vertical BEARING - HOLE DIAMETER 100mm ()	GROUND LEVEL RL 27 LOCATION 32759			.77m E 150435 N an Height Datum
DRILLING		STRA	TA		MATERIAL DESCRIPTION		CONDIT	ION	OBSERVATION
SAMPLE, TEST, BIT, SUPPORT, ETC.	R.L.	DEPTH m	GROUP SYMBOL	LEGEND	SOIL TYPE Plasticity / Grain Size, Colour, Minor Components	WATER / MOISTURE	COHESIVE	COHESIVE	SOIL ORIGIN, STRUCTURE, ETC.
SPTLS N=41 10;16,25  SPTLS N=41 12;17,24  SPTLS N=106* 28;30/85	3.07 -	m — — — — — — — — — — — — — — — — — — —	SM		Silty MUDSTONE, very low strength, extremely weathered, dark- grey-brown heavy ironstaining, properties of Silty CLAY (CH) hard, lenses of sandy ironstone. (continued)  Silty SAND (SM) very dense, fine to medium grained, light grey-orange, quartz sand.  Borehole completed at 26.235m depth	D-M	NS		SNDGRV
NOTES Hole Diameter 100mm to 26.24m depth. (150mm Auger to 14m then 100mm washbore to full depth) silty sands collapsing continuously throughout drilling									