COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department and author as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence, prepared by Arup". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

This log has been contributed to the Queensland Geotechnical Database with the permission of Arup.

ARU			L					HOLE				OF 1	
	DMR	DMR Ipswich Motorway Upgrade Wacol to Darra						LOGGED BY CHECKED BY				AT GWB	
CONTRACTOR		ratest	y opg.		ANGLE Vertical	DRILLED DATE 08-Apr-08 GROUND LEVEL RL 69.84m							
DRILL MODEL DRILLER	Edson 3000 Terratest				BEARING - HOLE DIAMETER 100mm ()	LC	LOCATION ELEVATION DATU			32091 E 144223			
DRILLER		Talcol			TIOLE BUNNETER TOOMIN ()						Local		
DRILLING		STRA	TA		MATERIAL DESCRIPTION			CONDITIO				OBSER	
			BOL			111	CONSIS		SISTI	TENCY			
SAMPLE, TEST, BIT, SUPPORT,	R.L.	DEPTH	GROUP SYMBOL	LEGEND	SOIL TYPE Plasticity / Grain Size, Colour, Minor Components	TER /	COHESIVE			NON		SOIL O	
ETC.				LE		WATER / MOISTURE	S S L S T J J W G						
	m	m	25		SAND, loose, medium to coarse grained, brown, with gravel subangular, with trace XW Sandstone fragments.	M	% s	<u>г</u> 22	/ 	≓ _ : I I	<u></u>	NON	
	-				- with trace XW Sandstone fragments.								
-	-	<u> </u>			-	-							
-	-					-							
SPTLS N=5 3;2,3	_	T1		· · · · · · .	- -]		$ \ \ $					
-		1			-	-							
		İ			_								
_	_	-2				-							
	-	1				-							
		İ		. · . · .	_								
	-	+			_	-							
	_	-3			_	1							
	-	Ī		. : . : .	-]							
	-	+				-							
	65 84 -	4 4.00				1							
SPTLS N=7 3;3,4	-		SC	<u>-::</u> -	Silty SAND (SC) loose, red, low plasticity fines with trace clay.	-						NON	
	-	1		F:_::		1							
	-	Ī		<u>.</u> :-::]							
	-	- 5			5.00m - 6.50m red brown.	-							
	-	<u> </u>		.	-								
		+		-∵ -∵	-	-							
	-	1		<u> </u>		1							
	-	-6		. ' - '	6.00m clay content decreases to Silty SAND	-							
-	63.34	6.50	0144			_						NON	
	-	<u> </u>	SW		SAND (SW) loose, fine to medium grained, light brown.	1						NON	
SPTLS N=8	62.84 -	7 7.00			Borehole completed at 7m depth		+						
4;4,4	-	+			<u>,</u>	1							
	-	Ī			-]							
SPTLS N=8 4;4,4		+				-		$ \ \ $					
- - - -	-	-8			<u>-</u>	1							
		<u> </u>				-		$ \ \ $					
	-	†			-	1		$ \ \ $					
	_	9			-]		$ \ \ $					
-		†			-	-							
	-	<u> </u>			<u> </u>	1							
								$ \cdot $					