COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



PROJECT

ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BOF 075:191/95

BOREHOLE	No	;	136
SHEET		;	1 OF 1
REFERENCE	Nο		H8200

: SOUTH EAST TRANSIT PROJECT - SECTION1 : 3120.478E 163457.912N LOCATION C60128 SURFACE R.L. : 18.84 DRILLER : DALY BROTHERS PTY LTD PROJECT No : JOB No DATUM : AHD DATE DRILLED : 30/01/98 INTACT DEFECT ROD DRILLING R.L. ADDITIONAL DATA STRENGTH SPACING LOG ()% (m) MATERIAL DEPTH AND GRAPHIC SAMPLES TESTS CORE DESCRIPTION TEST RESULTS 88888 REC* 짪ェਬ그럭 0 18.84 BITUMEN/ASPHAL PHYLLITE PHYLLITE DARK GREY TO BLUE GREEN MEDIUM TO COAR-SE GRAINED FOLIATED METASEDIMENTARY ROCK FOLIATION PLANE 40-70 DEGREES, IRREGULAR HW TO CONTORTED. HW : Yellow brown to mottled grey rock kernals & less sandy silty clay matrix 30/90 N →50 17.74 1 MW : Ornge brown to blue grey, vertically foliated with one HW zone. Is(50)=0.48MPa (43%) XW zone. 100 МЫ Is(50)=1.36MPa HW zone. . 2 16.51 (89%) Is(50)=0.56MPa 100 Drak grey to blue green. Partly to completely red brown ironstining only along defects. Discontinuous dark (mica) and 3 white quartz mineral layering throughout Is(50)=1.04MPa Defetcs : Major - Foliation partings (30-70 deg) Subhorihontal (<20 deg.) Minor - 60 to 70 deg. (83%) 100 Is(50)=0.82MPa Is(50)=2.45MPa 11.54MPa UCS Is(50)=1.21MPax (83%) 100 SW Is(50)=0.9MM&a Pressuremeter Test at 6.50m (92%) 100 Is(50)=2.54MPa Is(50)=1.45MPa (88%) 100 HW zone. Is(50)=0.93MPaх Is(50)=1.21MPaх (94%) 4.23MPa ucs 9.74 100 END OF HOLE REMARKS : LOGGED BY Please refer attached sheet/s for defect descriptions. DISS



DEFECT DESCRIPTIONS OF BORELOGS

[FOR GEOTECHNICAL TERMS AND SYMBOLS

REFER FORM BQF 075:191/95]

BOREHOLE NO :	вн136
SHE ET :	1 of 2
REFERENCE NO :	H8200

PROJECT : SOUTH EAST TRANSIT PROJECT -SECTION 1

LOCATION : 3120.478E 163457.912N

PROJECT NO : C60128 SURFACE R.L : 16.84 DRILLER : DALY BROTHERS P/L

JOB NO : DATUM : AHD DATE DRILLED : 28/1/98

DEPTH	DEFECT TYPE	APPRO. DIP ANGLE (Deg)	PLANARITY	ROUGHNESS	APERTURE	WALL ALTERATION	OTHER
1.53	FP	55	P	Sm	Т		
1.81 - 1.90							XW Zone
2.00	FP	70	P	Sm	0		QZ
2.28	FP	60	Ir	R		PFeSt	
2.58	J	0	Ir	R	0		
2.63	J	10	P	Sm		PFeSt	•
2.63	J	10	Ir	R			
3.05	FP	50	P	Sm	С	PFeSt	
3.42	FP	40	Ir	R			
3.63	J	<10	Ir	R			
3.70-3.75							XW Zone
3.83	J	60	P	Sm	Т		
4.17	J	<10	St		T	PFeSt	
4.64	J	10	P	R		H1	
4.7	J	10	P	R	Т		
4.74	FP	50	P	Sm	0	SM	
4.79	J	10	St	R	С		
4.89	FP	45	Ir	R	С		QZ
5.00	FP	10	Ir	R	0	PFeSt	

Abbreviations

	ROUGHNESS WALL ALTERATIONS			TYPE	OTHER		
R	Rough	FeSt	Iron Stained	J	Joint	P	Partly
Sm	Smooth	w	Weathered	В	Bedding	QZ	Quartz Vein
SL	Slickensided			FP	Foliation Parting	Co	Completely
				Fr	Fracture	In	Incipient
PLANARITY APERTURE		SZ	Sheared Zone	SI	Sand Infill		
Pl	Planar	С	Closed	WS	Weathered Seam	Н	Horizontal
St	Stepped	0	Open	CZ	Crushed Zone	V	Vertical
Un	Undulating	F	Filled	SM	Secondary Mineralisation	CI	Clay Seam
Cu	Curved	Т	Tight	BZ	Broken Zone	Cn	Clean
Ir	Irregular			HFZ	Highly Fractured Zone		

NOTE: This sheet should be read in conjunction with appropriate Engineering Borelog.



DEFECT DESCRIPTIONS OF BORELOGS

[FOR GEOTECHNICAL TERMS AND SYMBOLS

REFER FORM BQF 075:191/95]

BOREHOLE N	0 :	BH136	
SHEET	: _	2 of 2	-
REF EREN CE I	NO :	H8200	-

PROJECT : SOUTH EAST TRANSIT PROJECT - SECTION 1

LOCATION : 3120.478E 163457.912N

PROJECT NO : C60128 SURFACE R.L : 16.84 DRILLER : DALY BROTHERS P/L

JOB NO : DATUM : AHD DATE DRILLED : 28/1/98

DEPTH	DEFECT TYPE	APPRO. DIP ANGLE (Deg)	PLANARITY	ROUGHNESS	APERTURE	WALL ALTERATION	OTHER
5.35	J	<10	Ir	R	0		Cl
5.43	J	10	Ir	R	0		
5.55	J	20	St	R	С		<u> </u>
5.69	J	10	P	S		CFeSt	
6.20	J	80	Ir	R	0	CFeSt	
6.20	J	10	Ir	R	С	PFeSt	
6.69	J	20	St	R	С	SM	
7.03	Fr		Cu	R	Т		
7.26	FP	55	St		Т		QZ
7.45	FP	60	Ir				QZ (20mm)
7.55 - 7.63				R			
7.78	FP	45	Cu	R	Т	PFeSt	
7.80	FP	45	Cu	R	Т	CFeSt	
8.22	Fr		Cu	R	0		
8.32	J	70	P	R	0	CPFeSt	
8.32	J	<10	Ir	R	0	CFeSt	
8.40	Fr	20	St	R	0	PFeSt	
8.60	J	40	St	R	0	CFeSt	
9.00	Fr	<10	Cu		С	PFeSt	

Abbreviations

	ROUGHNESS WALL ALTERATIONS			TYPE		OTHER	
R	Rough	FeSt	Iron Stained	J	Joint	P	Partly
Sm	Smooth	W	Weathered	В	Bedding	QZ	Quartz Vein
SL	Slickensided			FP	Foliation Parting	Co	Completely
				Fr	Fracture	In	Incipient
	PLANARITY APERTURE		SZ	Sheared Zone	SI	Sand Infill	
Pl	Planar	C	Closed	ws	Weathered Seam	Н	Horizontal
St	Stepped	0	Open	CZ	Crushed Zone	V	Vertical
Un	Undulating	F	Filled	SM	Secondary Mineralisation	CI	Clay Seam
Cu	Curved	Т	Tight	BZ	Broken Zone	Cn	Clean
	Irregular			HFZ	Highly Fractured Zone		

NOTE: This sheet should be read in conjunction with appropriate Engineering Borelog.



