COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department and author as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence, prepared by Arup". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

This log has been contributed to the Queensland Geotechnical Database with the permission of Arup.

CLENT DMR COORES MALess GAR PROJECT PERVICENT MOTORWAY UPGRADE - WACKLIT DI DARA COORES MALess GAR COORES MALess GAR CONTRACTOR Termate Essension Termate Essension Termate Essension COORES MALess GAR COORES MALess GAR DELLEN Termate Essension Termate Essension Termate Essension COORES MALess GAR COORES COORES MALess GAR DRILLING STATA MATERIAL DESCRIPTION COORES CORES CORES SRIE SIGNAL TYPE BARMEL TEN; IFTC R.L. DEFT R.L. DEFT SRIE SIGNAL TYPE SRIE SIGNAL TYPE CORES CORES CORES SRIE SIGNAL TYPE SRIE SIGNAL TYPE CORES CORES CORES SRIE SIGNAL TYPE SRIE SIGNAL TYPE CORES CORES CORES SRIE SIGNAL TYPE CORES SRIE SIGNAL TYPE CORES CORES CORES SRIE SIGNAL TYPE C	ARU			BOREHOLE RECORD				BH319		OF 1	
PHOLECT PENUCH MOTORWAY UPCRADE - WACOL TO DARRA OHICKER BY MOLECT OLICITIE BY MOLECT OHICKER BY BY MOLECT OLICITIE BY MOLECT OHICKER BY MOLECT OLICITIE BY MOLECT OLICITIE BY MOLECT OUT BY MOLECT OUT	CLIENT	DMR							MAJ		
CONTRACTOR DRULLADOR Terested Econo 3000 D C Zemman Model BEARING BEARING HOLE DUALTIC HOLE			СН МОТС	DRW	AY UPGRADE - WACOL TO DARRA		- CHECKED BY GW			'B	
DRILLENCE Eden around DRILLER Eden around DRILLER 22227 E 1533 LocAtron Km X 22227 E 15337 LocAtron Km X 22227 LocAtron Km X	CONTRACTOR										
DRLING STRATA MATERAL DESCRIPTION CONDENSATION DBSE SMPLE TEST, IT. GLEPOTT TC. R.L DEPTH B B B B B B B B B B B B B B B B B B B	DRILL MODEL	Edson 3000				BEARING -		LOCATION 32237			
SMPLE TEST (T. CLUPORT, T.	DRILLER	DC	Joieman			HOLE DIAMETER 150mm ()					
SMPLE TEST (T. CLUPORT, T.			STDV-	гл				CONDIT			
SPTLS 22.0 0.02 SW 1.2 TOPSOL loss: SW M M SPTLS 21.0 1 0.00 SW 1.0 Compared for lossing gain adducted to subarguity, mediam dorse, red troom, graved for lossing gain adducted to subarguity, mediam dorse, red troom, graved for lossing gain adducted to subarguity, mediam dorse, red M SPTLS 21.00 1 0.00 CO Topsel SMD (SD) mediam to coarse grain adducted to subarguity, mediam dorse, red D SPTLS 10.00 CO Topsel SMD (SD) mediam to coarse grain, mediam dorse, red D D SPTLS 11.00 CO Topsel SMD (SD) mediam to coarse grain adducted box mediam dorse, red D D SDS 118.00 3 3.00 Exception adducted addered box mediam dorse, red D D SDS 118.00 3 3.00 Exception adducted addered box mediam dorse, red D D SDS 118.00 5.00 F SAMDSTONE: fire to mediam grained, we plasticity. D D M SDS 116.00 5.00 F SAMDSTONE: fire to mediam grained, we plastic	DIVIELING				Т	MATERIAL DESCRIPTION		CONDITION		OBSERVA	
SPT1.5 H-13 10.07 22.00 21.07 0.02 10.00 SV SV SV SV SV SV SV SV SV SV SV SV SV S	SAMPLE TEST			MBOL			≍ ⊟	CONSIS	STENCY	SOIL ORIG	
SPT1.5 H-13 10.07 22.00 21.07 0.02 10.00 SV SV SV SV SV SV SV SV SV SV SV SV SV S	BIT, SUPPORT,	R.L.	DEPTH	γSc	GEN		ATEF STU	COHESIVE		STRUCTU	
SPT1.5 H-13 10.07 22.00 21.07 0.02 10.00 SV SV SV SV SV SV SV SV SV SV SV SV SV S	ETC.			INOS	1 1	· · · · · · · · · · · · · · · · · · ·	ЗЙ			EIC.	
SPTLB 22.80 0.20 SW Excells SAMD (SX) median to coverse grain, median decade, and the coverse grain, median decay grain, decade, and the coverse grain, median decay grain, decade, and the coverse grain, median decay grain, decay and the coverse grain, median decay and the coverse grain, median decay and the coverse grain, decay and the coverse grain and the decay and the coverse grain, decay and t		m	m	9 GF	1.1.1.1	TOPSOIL, black.		ຬຬຬຬ	IN IN	TOP	
SPTLS N=19 21.70 21.90 1.10 0.00 col col col col col col col col col col		22.60	0.20	SW		Gravelly SAND (SW) medium to coarse grain, medium dense, red				COHE	
SPTLS N-13 5.87 21.80 1.00 1 0.80 50 - - - Clayey SAND. GkC) medium to cases grait, medium desise, red SMP CLY (CH) saft, grey, heavy trontaking. D D NO SPTLS 1.80 4 - Safty CLY (CH) saft, grey, heavy trontaking. D D Clayey SAND. SC) medium to cases grait, medium desise, red D Clayey SAND. SC) Clayey SAND. SC) D D M M SC) SC) SC) SC) SC) SC) Clayey SAND. SC) D D D D M M SC) SC) SC)			+			brown, gravel fine to coarse grain subrounded to subangular, with	1				
SPTLS N-10 5.0.7 21.70 1.10 1.00 5.00 SC CH Clayer SAND (SC) medium to coarse grain, medium dense, red SNP CLAY (CH) sett grey, heavy ronstaining D D 2.0.30 2.50 N0 Clayer SLT (M) very sett, grey, heavy ronstaining D D Clayer SLT (M) very sett, grey, heavy ronstaining D SDS 10.80 -2 N0 Clayer SLT (M) very sett, grey, with tace increative gravel. D D Clayer SLT (M) very sett, grey, with tace increative gravel. D SDS 10.80 -3 3.00 X SLSICNE, externally weathered, externally to attempt, grey with with pockeds of MOSTONE free grants. D D M SPTLS 13.07/200 -4 SLSICNE, free to medium graned, very low attempt, red brown. D D SDS 17.00 5.80 -5.80m extremely low strength. D D SNI SDS 11.40 7.40 SAUDSTONE, free graned, extremely low strength, red brown. D D D SNI SDS 11.400 5.800 -5.80m extremely low strength. D D SNI SDS 11.400 5.800 -5.80m extremely low strength. D <td></td> <td></td> <td>†</td> <td></td> <td> · ·</td> <td> 0.50m - 0.70m band of Clayey SAND, Black, Wet</td> <td>1</td> <td></td> <td></td> <td></td>			†		· ·	0.50m - 0.70m band of Clayey SAND, Black, Wet	1				
SPTLS N-110 CH Comparison Compa		21.90	0.90	SC		Clavey SAND (SC) medium to coarse grain medium dense red	-			NONCO	
SDS 13.80 4.80 SANDSTONE, fine to medium grained, very low strength, extremely low strength, extreme	SPTLS N=13 5:6 7	21.70	1.10		× ×	brown,.				COHE	
SDS 2.50 M M X Clayey SLT (M) very stiff, grey, with trace increating gravel. D D D D M X Strate CCO SDS 19.60 3 3.00 X Strate Strate D D D D M M X Strate D D D M M M X Strate D D D M M M M X Strate D D D M <			ļ		×××	Silty CLAY (CH) Stiff, grey, heavy ironstaining.					
SDS 2.50 M M X Clayey SLT (M) very stiff, grey, with trace increating gravel. D D D D M X Strate CCO SDS 19.60 3 3.00 X Strate Strate D D D D M M X Strate D D D M M M X Strate D D D M M M M X Strate D D D M <							-				
SDS 2.50 M M X Clayey SLT (M) very stiff, grey, with trace increating gravel. D D D D M X Strate CCO SDS 19.60 3 3.00 X Strate Strate D D D D M M X Strate D D D M M M X Strate D D D M M M M X Strate D D D M <			+		× ×	-	-				
SDS 19.80 -3 3.00		-	-2			-	-				
SDS 19.80 -3 3.00			†				1				
SDS 19.80 -3 3.00		20.30	2.50				-			СОНЕ	
SDS 19.80 3 0.00 SILTONE externely usedhered, externely tow strength, grey white SPTLS 13.57280 4 4 Solution of the strength			†	MI	× ×	L Gayey SILT (IVII) very su∏, grey, with trace ironstone gravel.	1				
SUS 10.5 10.5 10.5 10.5 10.5 10.5 10.5 10.5		10.00	3 200		×××						
SPTLS 13.57/290 SPTLS 13.57/290 18.00 4.80 SANDSTONE, fine to medium grained, very low strength, red brown, D SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange motile. SDS 14.80 8 8.00 Borehole completed at 8m depth SNE SDS 14.80 8 8.00 SNE	SDS	19.80 -	- 3 3.00		$\left \begin{array}{c} \times \times \\ \times \end{array} \right\rangle$	SILSTONE, extremely weathered, extremely low strength, grey white, with pockets of MUDSTONE and 10mm lenses of SANDSTONE fine	D			MUD	
SPTLS 13.57/290 SPTLS 13.57/290 18.00 4.80 SANDSTONE, fine to medium grained, very low strength, red brown, D SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange motile. SDS 14.80 8 8.00 Borehole completed at 8m depth SNE SDS 14.80 8 8.00 SNE			ļ		× × ×	grained, with ironstone gravel, low plasticity.					
SPTLS 13.57/200 4.80 SANDSTONE, fine to medium grained, very low strength, red brown. D D SNL SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely D SNL SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely SNL SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely SNL SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely SNL SDS 15.40 7.40 Clayey SANDSTONE, medium to coarse grained, very low strength, extremely SNL SDS 14.80 8 8.00 Borehole completed at 8m depth Image: additioned and additioned and additioned add			+				-				
SPTLS 13.57/200 4.80 SANDSTONE, fine to medium grained, very low strength, red brown. D D SNL SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely D SNL SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely SNL SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely SNL SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely SNL SDS 15.40 7.40 Clayey SANDSTONE, medium to coarse grained, very low strength, extremely SNL SDS 14.80 8 8.00 Borehole completed at 8m depth Image: additioned and additioned and additioned add			+				-				
SDS 17.0 4.80 5.80 5.80 5.80 5.80 5.80 5.80 5.80 5		-	- 4		$I \times X >$	<u>+</u>	-				
SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange mottle, SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange mottle, SDS 15.40 7.40 Clayey SANDSTONE, medium to coarse grained, very low strength, 15.40 7.40 Borehole completed at 8m depth SDS 14.80 8 8.00 Borehole completed at 8m depth	13;57/290		+		$ \times \times \rangle$		-				
SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange motile. SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange motile. SDS 14.80 8.00 Borehole completed at 8m depth			†				1				
SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange motile,. SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange motile,. SDS 15.40 7.40 Clayey SANDSTONE, medium to coarse grained, very low strength, 15.40 7.40 Clayey SANDSTONE, medium to coarse grained, very low strength, 15.40 7.40 Borehole completed at 8m depth		18.00	1 4 90		$ \times \times \rangle$						
SDS 17.00 6 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange motife. SDS SPTLS 16;46/295 15.40 7.40 Clayey SANDSTONE, medium to coarse grained, very low strength, light orange, with gravel fine grained subangular. SDS 14.80 8 8.00 Borehole completed at 8m depth SNE						SANDSTONE, fine to medium grained, very low strength, red brown,.	D			SNDST	
SDS 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange mottle,. SNI SDS			ļ -			-	-				
SDS 17.00 5.80 17.00 5.80 Clayey SANDSTONE, fine grained, extremely low strength, extremely weathered, grey orange mottle,.			+			5.30m - 5.80m extremely low strength	-				
SDS SPTLS N=47* 16,46/295 15.40 7,40 SDS 14.80 8 8.00 Borehole completed at 8m depth 	SDS		+			-	-				
SDS SPTLS N=47* 16.46/295 15.40 7.40 Clayey SANDSTONE, medium to coarse grained, very low strength, light orange, with gravel fine grained subangular. SDS 14.80 8 8.00 Borehole completed at 8m depth 9		17.00	- 5.80				-			SNDST	
SPTLS N=47* 15.40 7.40 SDS 14.80 8 8.00 9 9 16,46/295 14.80 7.40 15.40 7.40 15.40 7.40 15.40 7.40 15.40 7.40 16 Clayey SANDSTONE, medium to coarse grained, very low strength, light orange, with gravel fine grained subangular. Borehole completed at 8m depth		-	+6				-				
SPTLS N=47* 15.40 7.40 SDS 14.80 8 8.00 14.80 8 8.00 14.80 14.80 15.00 14.80 15.00 15.00 1			†			+	1				
SPTLS N=47* 15.40 7.40 SDS 14.80 8 8.00 14.80 8 8.00 14.80 8 100 14.80 8 100 14.80 7.40 15.40 7.40 14.80 7	SDS		1]				
SDS 16,46/295 15,40 7,40 SDS 14,80 8 8.00 Borehole completed at 8m depth 9 14.80 4 14.80 4 14.8	-		ļ			-					
SDS 16,46/295 15,40 7,40 SDS 14,80 8 8.00 Borehole completed at 8m depth 9 14.80 4 14.80 4 14.8	ерті с N=47*	-	-7			-	-				
SDS 14.80 8 8.00 Borehole completed at 8m depth			+			-	-				
SDS 14.80 - 8 8.00 Borehole completed at 8m depth		15.40	7.40			Clayey SANDSTONE, medium to coarse grained, very low strength	-			SNDST	
SDS 14.80 8 8.00 Borehole completed at 8m depth Image: Completed at 8m depth 9 Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth Image: Completed at 8m depth			+			light orange, with gravel fine grained subangular.	1				
14.80 -8 8.00 Borehole completed at 8m depth - - - - <	SDS		†		::::	F	1				
		14.80 -	8 8.00			Borehole completed at 8m depth				•	
			Į		1	-]				
			ļ		1	-					
						-	-				
		-	-9			-	-				
			+		1	-	-				
			+		1	F	-				
			†		1	-	1				
			†			-	1				
NOTES Hole Diameter 150mm to 8.00m depth. (150mm Auger to full depth) JOB	NOTES Hole Diar	neter 15	0mm to 8	00m c	lepth (1	50mm Auger to full depth)			JOB		

(c) State of Queensland (Department of Transport and Main Roads) 2020, CC BY 4.0. Please note copyright and limitation of liability notices on attached cover page.