## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department and author as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2023, licensed under the CC BY 4.0 Licence, prepared by ENGEO". This licence does not apply to logos or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

This log has been contributed to the Queensland Geotechnical Database with the permission of ENGEO.

## **LOG OF TEST PIT S-TP01** In Accordance with AS1726:2017 Client: Aussie Hydrovac Services Logged By: RC Beaudesert-Beenleigh Road Upgrade Date: 02/06/2021 Reviewed By : JA Beaudesert-Beenleigh road Test Pit Depth: 2.2 m Easting (MGA94): 519108.112 Beenleigh Excavator Type/Size : Bucket Excavator Northing (MGA94): 6933158.776 18840.000.001 Bucket Type/Size: 450mm Datum / Surface RL: AHD/34.364 m Stratigraphic Unit Shear Vane (kPa) Peak/Remolded Excavatability (Relative Scale) Dynamic Cone Depth (m BGL) Symbol Moisture Cond Consistency/ Density Index Elevation (RL) Type Penetrometer (DCP) Water Level Log Symbol Test DESCRIPTION Results Blows per 100mm Sample . Group 9 6 8 10 12 4 Sandy CLAY with Gravel and Cobbles (Topsoil) TOPSOIL St Brown, moist, stiff. Medium plasticity fines, fine to medium Sand, coarse, angular gravel, subangular Η cobbles VSt CI Sandy CLAY with Gravel and construction waste (Fill) Brown, moist, stiff. 0.5 Medium plasticity fines, fine to medium sand, medium subangular gravel, angular cobbles, roots throughout. CLAY trace Sand trace Gravel (Alluvium) Red brown, moist, very stiff. Medium plasticity fines, fine to medium sand, fine to coarse, subangular to angular gravel 1.0-M VSt BULK (A CI -33 1.5 2.0 Depth of Excavation: 2.2 m Termination Condition: Proximity to telstra cable 2.5

Testpit length and depth retricted due to telstra cable