COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



TEST PIT LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/5-2009

PRO	DJECT	_	B <u>ruce</u>	Highway Cooroy to Curra Section A Geotechnical Investigation					
			Southern I/C, Embankment 1B COORDINAT				ES 491253.2 E, 7076438.2 N		
PRO	DJECT	No_				SYSTEM	MGA94_		
JOE	No		128/1	DA/901 EQUIPMENT TYPE AND MODEL Hitachi 5	T Tracked Excavator	BUCKET SIZE	_450mm_		
DEPTH (m)	(m)	МЕТНОБ	RING	SOIL DESCRIPTION SOIL TYPE: Colour, grain size, plasticity or particle characteristics, moisture, consistency, density, secondary components	DCP LOG	ADDITIONAL DA	ATA	SAMPLE NUMBER	REPORT
o DEP	109.93		USC WEATHERING	ROCK DESCRIPTION ROCK SUBSTANCE: Type, colour, grain characteristics, weathering, strength, structure, inclusions	(Blow Count / 100mm 0 4 8 12 16>2		JLTS	SAMPLE	TEST RE
1	109.78		CL- CI	Silty CLAY (Topsoil) Pale brown to red brown, moist, firm, low to intermediate plasticity Silty CLAY (Fill?) Pale grey to brown, wet, stiff. Low to intermediate plasticity; trace fine to medium gravel consisting of subangular to angular chert and quartz; rootlets; occasional wood fragments up to 150mm dia		Seepage 0.6 to 1.2 fast inflow in all pit	m faces.		
	108.73		мн	Clayey SILT (Residual Soil?) Red brown to pale and orange brown with pale grey mottling, moist, stiff to very stiff. High plasticity; occasional rootlets; becoming dry to moist below 1.5m.		Pit spalling at 1.2m; seepage fast inflow. LL = 60; PI = 29; LS = 15.6; MC = 30.5%; WPI = 2654	<i>i</i> .	A	D,Bulk
-2	107.83			Below 2.0m: Becoming very stiff to hard.		Pit spalling from 2.	1 to		2
-				Gravelly CLAY with Silt (Residual Soil)	1	3.1m.			
				Pale grey with orange brown and red brown mottling, moist, very stiff to hard.		MC = 25.3%		В	D,Bulk
			CL	Low plasticity; gravel fraction is angular, fine to coarse grained consisting predominanity of quartz. At 3.0m: Possible seepage at base of gravel; slight organic					
-3	106.83			odour and dark brown pockets.					
	106.28		СІ	Silty CLAY (Residual Soil) Pale grey with red brown and orange brown mottling, moist, very stiff to hard. Intermediate plasticity; trace fine to course grained, subangular to angular quartz gravel; slight organic odour.					
				Excavation terminated at 3.65m					
4	105.93								
			Testpit Profile Excavated Mater						
				John Marian Control of the Control o		The second secon			
REMARKS FSV= Field shear vane (Peak/residual);							LOGGED BY BJD		