

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>



**Queensland
Government**

**GEOTECHNICAL
BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No **BH264**

Sheet 1 of 3

REFERENCE No **H12273**

PROJECT Mackay Ring Road
 LOCATION Fursden Creek Bridge, Pier 2 (LHS) COORDINATES 721480.0 E; 7661443.4 N
 PROJECT No FG6184 SURFACE RL 5.39m PLUNGE 90° DATE STARTED 02/08/2015 GRID DATUM GDA 94 / MGA 255
 JOB No 242/10G/906 HEIGHT DATUM A.H.D. BEARING ° DATE COMPLETED 03/08/2015 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASHBORING CORE DRILLING	RQD (%) CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USCS WEATHERING	INTACT STRENGTH	DEFECT SPACING	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS		
												EH	VH
1				A	Silty CLAY trace sand (Topsoil) Dark brown, dry, firm. Fine grained sand, medium plasticity. trace roots and rootlets. 1.10m: becomes stiff to very stiff	(CI)					5, 7, 7 N=14	SPT	
2	3.29			B	Sandy SILT (Alluvium) Brown, dry, very stiff. Fine grained sand, low plasticity.	(ML)					6, 8, 8 N=16	SPT	
3	2.59			C	SAND trace clay (Alluvium) Pale orange grey, dry, medium dense. Fine to medium grained sand.						7, 8, 8 N=16	SPT	
4				D	4.00m: becomes medium grained sand.	(SW)					6, 9, 12 N=21	SPT	
5	0.09			E	5.00m: becomes fine to coarse grained sand.						11, 10, 11 N=21	SPT	
6				F	Silty SAND (Alluvium) Grey, wet, medium dense to dense. Fine to medium grained sand.	(SM)					10, 15, 16 N=31	SPT	
7	-1.41			G	Sandy CLAY (Alluvium) Mottled orange brown and grey, moist, very stiff. Fine grained sand, medium plasticity.	(CI)					9, 12, 15 N=27	SPT	
8				H	8.00m: sand content increasing. Becomes clayey sand trace gravel. Fine grained gravel, rounded grains.						7, 9, 11 N=20	SPT	
9	-3.61			I	CLAY trace sand (Residual) Pale grey, moist, stiff. Fine grained sand, medium to high plasticity.	(CI)					5, 7, 7 N=14	SPT	
	-4.61												

Continued on next sheet

REMARKS: Kgwu = Wundaru Granodiorite

LOGGED BY	REVIEWED BY
C.Boyes	S.Foley



**Queensland
Government**

**GEOTECHNICAL
BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No **BH264**

Sheet 2 of 3

REFERENCE No **H12273**

PROJECT	Mackay Ring Road		
LOCATION	Fursden Creek Bridge, Pier 2 (LHS)	COORDINATES 721480.0 E; 7661443.4 N	
PROJECT No	FG6184	SURFACE RL 5.39m	PLUNGE 90°
			DATE STARTED 02/08/2015
			GRID DATUM GDA 94 / MGA Z55
JOB No	242/10G/906	HEIGHT DATUM A.H.D.	BEARING °
			DATE COMPLETED 03/08/2015
			DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	FAUGER CASING WASHBORING CORE DRILLING	RQD (%) CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USCS WEATHERING	INTACT STRENGTH	DEFECT SPACING	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS		
												EH	VH
-4.91				J	CLAY trace sand (Residual) (Cont'd)	(CI)					8, 10, 11 N=21	SPT	
					10.00m: sand content increasing								
				K	GRANODIORITE XW: Recovered as speckled pink, grey and dark grey, moist, medium dense, silty clayey sand. Fine to medium grained.						9, 11, 14 N=25	SPT	
				L	12.00m: becomes very dense.						18, 21, 30/140	SPT	
				M		XW					16, 28, 30/100	SPT	
				N							30, 30/90	SPT	
				O							28, 30/110	SPT	
				P							27, 30/140 hb	SPT	
-11.11				Q	GRANODIORITE HW: Pink, brown and white, coarse grained, massive, very low strength.						30, 30/40	SPT	
				R		HW					30/105 hb	SPT	
				S	19.00m: becomes orange brown speckled pale and dark grey.						30/60 hb	SPT	
-14.61													

Continued on next sheet

hb

REMARKS: Kgwu = Wundaru Granodiorite

LOGGED BY	REVIEWED BY
C.Boyes	S.Foley



Queensland Government

GEOTECHNICAL BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No **BH264**

Sheet 3 of 3

REFERENCE No **H12273**

PROJECT	Mackay Ring Road				
LOCATION	Fursden Creek Bridge, Pier 2 (LHS)			COORDINATES 721480.0 E; 7661443.4 N	
PROJECT No	FG6184	SURFACE RL	5.39m	PLUNGE	90°
				DATE STARTED	02/08/2015
				GRID DATUM	GDA 94 / MGA Z55
JOB No	242/10G/906	HEIGHT DATUM	A.H.D.	BEARING	°
				DATE COMPLETED	03/08/2015
				DRILLER	Saxon Drilling

DEPTH (m)	R.L. (m)	FAUGER CASING WASHBORING CONE DRILLING	RQD (%) CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USCS WEATHERING	INTACT STRENGTH	DEFECT SPACING	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS						
												EH		EC		EW	
												VH	H	VH	C	M	W
21				U	GRANODIORITE HW: (Cont'd)	+	HW				SPT						
	-16.61										30/50 hb						
22			(31)		GRANODIORITE SW: Speckled grey, dark grey and pink, medium to coarse grained, massive, high to very high strength. Js: 5° to 10° (<2/m); Pl/Ro; OP; some Fe St;	+	HW	VL	EL	22.10m: VN: 80°; CA	A (22.27m)						
			100				MW	VC	C	22.30m-22.34m: BZ:	A (22.56m)						
			(79)		Js: 20° to 35° (<3/m); Pl/Sm; OP; CA VN <1mm;	+		VC	C	22.75m-22.94m: VN: 90°; CA <10mm;	D (23.15m)						
			100		Js: 70° to 80° (<2/m); Pl/Sm; OP or CD; Fe St;	+		C	M	23.70m: Total Water Loss	A (23.05m)						
			(93)		24.00m: becomes dark grey	+	SW	H-VH	M	02/08/2015 UCS=59.10 MPa	(23.89m)						
24										24.51m: BZ: 5°; 10mm;	D (24.40m)						
25			100			+	MW	H	EC-VC	26.11m-26.15m: BZ: 5°; some Sinf;	D (25.18m)						
			(39)		26.08 to 26.52m: MICRODIORITE (MW): Grey, fine grained, massive, high strength. Calcite veinlets <2mm throughout. Locally fractured. Upper contact: 70°; Pl/Sm; OP; CA VN <4mm; Lower contact: 70°; Pl/Sm; CD;	+		H	C	26.33m-26.52m: BZ: Js: 70° to 80°; and 5° to 10°; CA VN: 80°; Pl/Sm; <5mm;	A (25.25m)						
26										26.52m-26.70m: VN: 80° to 90°; Un/Ro; CD; CA;	D (27.00m)						
27							SW	VH	M	27.15m-28.00m: VN: 90°; Un/Ro; OP; CA;	A (27.10m)						
28			100					VC	M		UCS=110.00 MPa						
	-23.01				Borehole completed at 28.40m						(28.00m)						
29																	

REMARKS: Kgwu = Wundaru Granodiorite


LOGGED BY	REVIEWED BY
C.Boyes	S.Foley

CORE PHOTO LOG

DEPARTMENT OF TRANSPORT AND MAIN ROADS
 Geotechnical Section
 35 Butterfield Street, Herston Qld 4006
 Phone 07 3066 3336



Project Name	Mackay – Ring Road (Stage 2)		
Project No.	FG6184	Date	03/08/15
Borehole No.	BH 264	TMR H No.	H12273
Location	Fursden Creek Bridge	Start Depth (m)	22.00
Detail	Pier 2, LHS	Finish Depth (m)	28.40
Chainage		Submitted By	M.Ensor
Remarks			



SCALE 1:5