COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



PROJECT

ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BQF 075:191/95

: SOUTH EAST TRANSIT PROJECT - SECTION 2

BOREHOLE No : 234

SHEET : 1 OF 2

REFERENCE No : H8172

LOCA PROJ		:ç	60117		52007.1N SURFACE R.L. : 14.85					ER : DALY BROTHERS PTY LTD	
JOB	No	:	50302CN	!	DATUM : AHD				RILLE	ED: 28/11/97	
о DEPTH (m)		AUGER CORE DRILLING CASING OTHER	RQD ()% CORE REC%	SAMPLE	MATERIAL DESCRIPTION	USC	INTACT STRENGTH	DEFECT SPACING (mm) 000- 000- 000- 000-	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES
	14.25				SUBBASE Pale brown gravelly silty clay.					Driller's log only	
1	13.48				XW TUFF XW: exhibits engineering properties of pale green, moist to dry, hard sandy silty clay; medium plasticity. isolated mottled zones; some gravel particles.	xw				10,20,30/70=>50	SPT -
2			(0) 100		HW TUFF Brown, corestones and rock kernels throughout.						1 1 1 1 1
-3	11.83								\bigvee	Is(50)=0.07MPa Sheared zone;F/D = 017/27 28/11/97	× , , , , , , , , , , , , , , , , , , ,
- 4			(20) 75			нw				Is(50)=0.05MPa	× -
-5			(95) 97	=						16.30MPa	UCS
6			(25)							Is(50)=0.03MPa	× ;
7	7.95		97	_	MW TUFF Orange brown; completely red-brown iron- staining.						
-8	6.35		(91) 100			MW				4.95MPa Is(50)=0.07MPa	ucs x
9			(67) 100							Is(50)=0.60MPa Is(50)=0.36MPa	x ;
RE	MARKS	• • • •		• • • •	ed list for defect descriptions. defect data were extracted from BIPS.			E88881		LOGGED BY DISS	



ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BQF 075:191/95

BOREHOLE No : 234

SHEET : 2 OF 2

REFERENCE No : H8172

JOB No		SURFACE R.L. : 14.85 DATUM : AHD			DALY BROTHERS PTY LTD 28/11/97			
(E) (m) (m)	RQD () %		ГΤ	INTACT STRENGTH	DEFECT	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES
4.15	POUD REC* S	MW TUFF as above	MW					VS F
-11	100	SW TUFF Pale green, massive, prophyritic texture	SW				Is(50)=1.41MPa	×
2.35	(100)			+	-		Is(50)=1.14MPa	×
		END OF HOLE						
- 14 14								
-15								
- - - - 16								
-17					- - - -			
- 18								
- 19					-			
20							LOGGED BY	



DEFECT DESCRIPTIONS OF BORELOGS

[FOR GEOTECHNICAL TERMS AND SYMBOLS

REFER FORM BQF 075;191/95]

BOREHOLE NO :	234
SHEET :	l of l
REFERENCE NO :	H8172

PROJECT SOUTH EAST TRANSIT PROJECT - SECTION 2

LOCATION : 4155.205E 162007.144N

PROJECT NO : C60117 SURFACE R.L : 14.75 DRILLER : DALY BROTHERS PTY LTD

JOB NO : 650302CN DATUM : AHD DATE DRILLED : 28/11/97

DEPTH	DEFECT TYPE	DIP(Degrees)	PLANARITY	ROUGHNESS	APERTURE	WALL ALTERATION	OTHER
8.25	J	15	Ir	R		CoFeSt	
8.39		15			Т	CoFeSt	
8.42	J	15	Ir	R		CoFeSt	
8 .72	_	15	Ir			CoFeSt	
8.95		20	Ir				Cn
9.7	J		Ir			CoFeSt	Н
9.85		_	Ir		T	CoFeSt	Н
10.15			Ir			CoFeSt	
10.21		15		R		CoFeSt	
10.28	J	15		, R		CoFeSt	•
				,			_
		_					

Abbreviations

	ROUGHNESS		WALL ALTERATIONS		TYPE	OTHER		
R	R Rough		FeSt Iron Stained		Joint	P	Partly	
Sm	Smooth	W	Weathered	В	Bedding	QZ	Quartz Vein	
SL	SL Slickensided				Bedding Parting	Со	Completely	
				F	Folliation	In	Incipient	
	PLANARITY		APERTURE	SZ	Sheared Zone	SI	Sand Intil	
PΙ	Planar	С	Closed	WS	Weathered Seam	H	Horizontal	
St	Stepped	0	Open	CZ	Crushed Zone	V	Vertical	
Un	Undulating	F	Filled	SM	Secondary Mineralisation	CI	Clay Intill	
Cu	Cu Curved		T Tight		Broken Zone	Cn	Clean	
Ir Irregular				HFZ	Highly Fractured Zone			

NOTE: This sheet should be read in conjunction with appropriate Engineering Borelog.


W:\Geomecha\Addisan\defdescr.sam









SOUTH EAST TRANSIT PROJECT BH 234 1.00 - 3.40 M




SOUTH EAST TRANSIT PROJECT BH 234 3.40 - 5.80 M




SOUTH EAST TRANSIT PROJECT BH 234 5.80 - 8.20 M



SOUTH EAST TRANSIT PROJECT BH 234 8.20 - 10.60 M



SOUTH EAST TRANSIT PROJECT BH 234 10.60 - 12.45 M





SOUTH EAST TRANSIT PROJECT, SECTION 2

WATER PRESSURE TEST RESULTS

2 LUGEONS

Drill Hole:

234

Date:

1/12/97

Test No:

1

From (m) To (m)

Length (m)

Test Section:

8.00

12.50

4.50

Groundwater Depth (m):

3.02


Gauge Height (m):

1.23

Hydrostatic Head (kPa):

42.5

Gauge Pressure (kPa)	Effective Pressure (kPa)	Test Duration (min)	Meter Start (litres)	Meter End (litres)	Water Loss (litres)	Leakage (1/m/min)	Lugeons
50	92.5	5	50.3	51.9	1.6	0.07	0.77
120	162.5	5	55.1	61.6	6.5	0.29	1.78
180	222.5	5	73.5	82.3	8.8	0.39	1.76
120	162.5	5	100	106.6	6.6	0.29	1.81
50	92.5	5	109.9	115.8	5.9	0.26	2.83





SOUTH EAST TRANSIT PROJECT, SECTION 2

WATER PRESSURE TEST RESULTS

<1 LUGEONS

Drill Hole:

234

Date:

1/12/97

Test No:

23 2

From (m)

To (m)

Length (m)

Test Section:

5.00

12.50

7.50

Groundwater Depth (m):

3.02

Gauge Height (m):

1.13

Hydrostatic Head (kPa):

41.5

Gauge Pressure (kPa)	Effective Pressure (kPa)	Test Duration (min)	Meter Start (litres)	Meter End (litres)	Water Loss (litres)	Leakage (1/m/min)	Lugeons
50	91.5	5	74.2	74.2	0	0.00	0.00
80	121.5	5	74.9	78.3	3.4	0.09	0.75
130	171.5	5	85.2	90.3	5.1	0.14	0.79
80	121.5	5	101	105.2	4.2	0.11	0.92
50	91.5	5	116.1	117.7	1.6	0.04	0.47

