

## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>



**Queensland  
Government**

Department of  
Main Roads

## ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No **BHP05**

SHEET **1** of **3**

REFERENCE No **H9898**

PROJECT **HOUGHTON HIGHWAY BRIDGE DUPLICATION - HOUGHTON HIGHWAY UPGRADE PROJECT**

LOCATION **24m RIGHT FROM EASTN PILE OF PIER 5 OF EXIST BRIDGE**

COORDINATES **38931.9 E; 52055.2 N**

PROJECT No **FG5423** SURFACE R.L. **-0.76** PLUNGE DATE STARTED **22/04/06** GRID DATUM **PROJECT DATUM**

JOB No **165/122/35** HEIGHT DATUM **AHD** BEARING DATE COMPLETED **22/04/06** DRILLER **CAIRNS DRILLING**

DEPTH (m)	R.L. (m)	CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
0	-0.76														
0.1					A	<b>ESTUARINE SAND &amp; SHELL</b> Dark grey to grey brown, wet, mainly very loose to loose.  Slightly organic in some places.							$pH_p = 8.05$ $pH_{Fox} = 6.79$	HW, 1,1 N=2 ASS Sample stored at Herston Geotechnical Laboratory	SPT
1.3					B		(SP-SM)						$pH_p = 8.02$ $pH_{Fox} = 6.63$	2,1,3 N=4 ASS Sample stored at Herston Geotechnical Laboratory	SPT
2.9	-3.16				C	<b>ESTUARINE SILTY SAND</b> Dark grey, wet, very loose.  Gradually becoming sandy silty clay with depth.			(SM)				$pH_p = 7.36$ $pH_{Fox} = 3.53$	HW N<1	SPT
4.5	-4.56				D	<b>ALLUVIAL SILTY SANDY CLAY</b> Mottled grey to yellow brown, moist, soft to firm.  Medium plasticity.			(CI)				$pH_p = 6.25$ $pH_{Fox} = 5.41$	2,1,3 N=4 ASS Sample stored at Herston Geotechnical Laboratory	SPT
5.8	-5.76				E	<b>ALLUVIAL SILTY CLAY</b> Grey green to mottled orange brown/red, moist, mainly very stiff.  Medium to high plasticity.							$pH_p = 4.70$ $pH_{Fox} = 3.35$	5,8,11 N=19 ASS Sample stored at Herston Geotechnical Laboratory	SPT
7.9					F									7,9,14 N=23	SPT
9.1					G									7,13,18 N=31	SPT
10.0	-10.76														

REMARKS **FINE GRAINED MAINLY LAMINATED SEDIMENTARY ROCK**

LOGGED BY  
BW / ADISS



**Queensland  
Government**

Department of  
Main Roads

## ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No **BHP05**

SHEET **2** of **3**

REFERENCE No **H9898**

PROJECT **HOUGHTON HIGHWAY BRIDGE DUPLICATION - HOUGHTON HIGHWAY UPGRADE PROJECT**

LOCATION **24m RIGHT FROM EASTN PILE OF PIER 5 OF EXIST BRIDGE** COORDINATES **38931.9 E; 52055.2 N**

PROJECT No **FG5423** SURFACE R.L. **-0.76** PLUNGE DATE STARTED **22/04/06** GRID DATUM **PROJECT DATUM**

JOB No **165/122/35** HEIGHT DATUM **AHD** BEARING DATE COMPLETED **22/04/06** DRILLER **CAIRNS DRILLING**

DEPTH (m)	R.L. (m)	CASING USING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	-10.76					<b>ALLUVIAL SANDY SILTY CLAY</b> Grey to mottled orange brown, moist, stiff to mainly very stiff.  Medium to high plasticity.						7,11,15 N=26	SPT
11													
12					J		(Cl-CH)					5,4,7 N=11	SPT
13					K							3,5,9 N=14	SPT
14	-14.76					<b>SANDSTONE</b> <b>FINE TO MEDIUM GRAINED MASSIVE TO MAINLY LAMINATED POORLY CEMENTED SEDIMENTARY ROCK</b> <b>XW:</b> Generally exhibits engineering properties of pale yellow brown to mottled orange brown, moist, mainly very stiff to hard silty clay.  Medium plasticity.  Gradually becoming hard with depth.						3,10,13 N=23	SPT
15					L								
16					M							3,6,9 N=15	SPT
17							XW						
18					N							3,6,13 N=19	SPT
19													
20	-20.76				P							7,16,30 N=46	SPT

REMARKS **FINE GRAINED MAINLY LAMINATED SEDIMENTARY ROCK**

LOGGED BY  
BW / ADISS



# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No BHP05  
SHEET 3 of 3  
REFERENCE No H9898


PROJECT HOUGHTON HIGHWAY BRIDGE DUPLICATION - HOUGHTON HIGHWAY UPGRADE PROJECT  
LOCATION 24m RIGHT FROM EASTN PILE OF PIER 5 OF EXIST BRIDGE COORDINATES 38931.9 E; 52055.2 N  
PROJECT No FG5423 SURFACE R.L. -0.76 PLUNGE DATE STARTED 22/04/06 GRID DATUM PROJECT DATUM  
JOB No 165/122/35 HEIGHT DATUM AHD BEARING DATE COMPLETED 22/04/06 DRILLER CAIRNS DRILLING

DEPTH (m)	R.L. (m)	CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
20	-20.76					<b>HW:</b> Pale orange brown to brown, moist, very dense silty sand gradually grading into very low to low strength rock.							
21												30/110 N>50	SPT
22												30/100 N>50	SPT
23													
24	-24.26		(100)			<b>MW:</b> Pale orange brown to brown, fine to medium grained, slightly massive to mainly laminated, mainly low to medium strength.  Defects: Generally rare. - Occasional drilling-induced lamination partings <10° (1-2/m).						Is(50)=0.18 MPa Is(50)=0.12 MPa Is(50)=0.21 MPa Is(50)=0.21 MPa Is(50)=0.20 MPa Is(50)=0.42 MPa Is(50)=0.29 MPa Is(50)=0.25 MPa	o x o x x o o x
25	-26.22		100 (93)			<b>MUDSTONE (See Remarks)</b> <b>MW:</b> Dark grey to black, fine grained, thinly laminated, mainly low to occasionally medium low strength. Defects: Frequent drilling-induced lamination partings <10° (6/m).						Is(50)=0.16 MPa Is(50)=0.22 MPa Is(50)=0.29 MPa Is(50)=0.19 MPa Is(50)=0.23 MPa Is(50)=0.44 MPa Is(50)=0.16 MPa	o x o o x x o
26	-27.21					<b>INTERBEDDED MUDSTONE AND SANDSTONE</b> <b>FINE TO MEDIUM GRAINED MAINLY LAMINATED POORLY CEMENTED SEDIMENTARY ROCK</b> <b>SW:</b> Dark grey, black to white banded, fine to medium grained, mainly laminated, mainly low to medium strength. Defects: Some drilling-induced lamination partings <10° (2/m).						Is(50)=0.66 MPa Is(50)=0.72 MPa Is(50)=0.13 MPa Is(50)=0.37 MPa Is(50)=0.25 MPa Is(50)=0.39 MPa Is(50)=0.69 MPa	x o x o o x o
27	-27.86												
28	-28.76		93			<b>MUDSTONE (As above.)</b> <b>MW:</b> Dark grey to black, fine grained, thinly laminated, very low to mainly low strength. Defects: Generally rare. - Occasional drilling-induced lamination partings <10° (1/m). Borehole terminated at 28m						Core left in the borehole	
29													
30													

REMARKS FINE GRAINED MAINLY LAMINATED SEDIMENTARY ROCK

LOGGED BY  
BW / ADISS

Project: **Houghton Highway Bridge Duplication**  
Borehole No: **BHP5**  
Start Depth: 23.50m  
Finish Depth: 28.00m  
Project No: FG5423  
H No: 9898



# Point Load Strength Index - Test Report

**Project: Houghton Highway Bridge Investigation**

**Project No: FG5423**

**Date Sampled** 17/05/06

**Feature: N/A**

**Sample Type: NMLC Core**

**Date Tested 06/06/06**

**Report No. FG5423/GS06-426/AS4133.4.1**

Sample Number	Sample Location	Depth (m)	Test Type D,A,B,I*	Is (MPa)	Is50 (MPa)	Strength Descriptor**	Lithology
GS06/426.A	BHP 05	23.85	A	0.18	0.18	L	Sandstone
GS06/426.B	BHP 05	23.88	D	0.12	0.12	L	Sandstone
GS06/426.C	BHP 05	24.15	A	0.22	0.21	L	Sandstone
GS06/426.D	BHP 05	24.18	D	0.21	0.21	L	Sandstone
GS06/426.E	BHP 05	24.55	A	0.42	0.42	M	Sandstone
GS06/426.F	BHP 05	24.50	D	0.20	0.20	L	Sandstone
GS06/426.G	BHP 05	24.90	A	0.28	0.29	L	Sandstone
GS06/426.H	BHP 05	24.95	D	0.25	0.25	L	Sandstone
GS06/426.J	BHP 05	25.38	A	0.16	0.16	L	Sandstone
GS06/426.K	BHP 05	25.40	D	0.22	0.22	L	Sandstone

Sample Remarks

\* D - Diametral; A - Axial; B - Block; I - Irregular;

\*\* EL - Extremely Low; VL - Very Low; L - Low; M - Medium; H - High; VH - Very High; EH - Extremely High ( taken from AS1726 Table 8A )

Remarks / Variations to Test Procedures:

\*\*\*\*\*  
\*\*\*\*\*  
\*\*\*\*\*

Test Method: AS4133.4.1

Software Version 2.03 April 2005

Client Name: Department of Main Roads  
Client Address: PO Box 70, Spring Hill QLD 4004

Signatory .....

( Peter W Reynolds )



Accreditation Number: 2302  
Accredited for compliance  
with ISO/IEC 17025

This document is issued in  
accordance with NATA's  
accreditation requirements.



# Point Load Strength Index - Test Report

**Project: Houghton Highway Bridge Investigation**

**Project No: FG5423**

**Date Sampled 17/05/06**

**Feature: N/A**

**Sample Type: NMLC Core**

**Date Tested 06/06/06**

**Report No. FG5423/GS06-426/AS4133.4.1**

Sample Number	Sample Location	Depth (m)	Test Type D,A,B,I*	Is (MPa)	Is50 (MPa)	Strength Descriptor**	Lithology
GS06/426.L	BHP 05	25.48	A	0.30	0.29	L	Mudstone
GS06/426.M	BHP 05	25.51	A	0.20	0.19	L	Mudstone
GS06/426.N	BHP 05	25.70	D	0.23	0.23	L	Mudstone
GS06/426.P	BHP 05	25.90	D	0.44	0.44	M	Mudstone
GS06/426.Q	BHP 05	25.95	A	0.16	0.16	L	Mudstone
GS06/426.R	BHP 05	26.42	A	0.70	0.72	M	Mudstone
GS06/426.S	BHP 05	26.40	D	0.67	0.66	M	Mudstone
GS06/426.T	BHP 05	26.50	D	0.13	0.13	L	Mudstone
GS06/426.U	BHP 05	26.52	A	0.39	0.37	M	Mudstone
GS06/426.V	BHP 05	26.85	D	0.43	0.39	M	Mudstone

Sample Remarks

\* D - Diametral; A - Axial; B - Block; I - Irregular;

\*\* EL - Extremely Low; VL - Very Low; L - Low; M - Medium; H - High; VH - Very High; EH - Extremely High ( taken from AS1726 Table 8A )

Remarks / Variations to Test Procedures:

Test Method: AS4133.4.1

Software Version 2.03 April 2005

Client Name: Department of Main Roads  
Client Address: PO Box 70, Spring Hill QLD 4004

Signatory .....

( Peter W Reynolds



Accreditation Number: 2302  
Accredited for compliance  
with ISO/IEC 17025

This document is issued in  
accordance with NATA's  
policy on document control

## Point Load Strength Index - Test Report

**Project: Houghton Highway Bridge Investigation**

**Project No: FG5423**

**Date Sampled 17/05/06**

**Feature: N/A**

**Sample Type: NMLC Core**

**Date Tested 06/06/06**

**Report No. FG5423/GS06-426/AS4133.4.1**

Sample Number	Sample Location	Depth (m)	Test Type D,A,B,I*	Is (MPa)	Is50 (MPa)	Strength Descriptor**	Lithology
GS06/426.X	BHP 05	26.83	A	0.25	0.25	L	Mudstone
GS06/426.Y	BHP 05	27.15	A	0.71	0.69	M	Mudstone

Sample Remarks

\* D - Diametral; A - Axial; B - Block; I - Irregular;

\*\* EL - Extremely Low; VL - Very Low; L - Low; M - Medium; H - High; VH - Very High; EH - Extremely High ( taken from AS1726 Table 8A )

Remarks / Variations to Test Procedures:


Test Method: AS4133.4.1

Software Version 2.03 April 2005

\*\*\*\*\*  
\*\*\*\*\*  
\*\*\*\*\*

Client Name: Department of Main Roads

Client Address: PO Box 70, Spring Hill QLD 4004

Signatory  16/6/06  
( Peter W Reynolds )



Accreditation Number: 2302  
Accredited for compliance  
with ISO/IEC 17025

This document is issued in  
accordance with NATA's