

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No BH173
SHEET 1 of 3
REFERENCE No 12114

PROJECT Mackay Ring Road Geotechnical Investigation - Stage 1
LOCATION Fursden Creek Overflow Bridge Pier 1; CH: 8710m; COORDINATES 721432.6 E; 7661030.2 N
PROJECT No FG6184 SURFACE R.L. 7.34m PLUNGE _____ DATE STARTED 20/10/14 GRID DATUM GDA 94 /MGA Zone 55
JOB No _____ HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/10/14 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH											DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
									EH	VH	H	M	J	VL	EL	EC	VC	W	VW	EW			
0	7.34					Silty CLAY (TOPSOIL) Dark brown, moist, stiff. Medium plasticity. Some roots.																	
1					A		(CI)															4.5,7 N=12	SPT
1.50	5.84					Silty SAND (ALLUVIUM) Brown, moist, mainly loose to medium dense. Fine to medium grained sand.																	
2					B																	2,4,4 N=8	SPT
3					C																	3,3,5 N=8	SPT
4					D		(SM)															4,4,4 N=8	SPT
5					E																	4,5,6 N=11	SPT
6					F																	2,4,5 N=9	SPT
7					G	7.00m: Becoming medium to coarse grained sand. Trace medium subangular gravel.																6,7,8 N=15	SPT
7.50	-0.16					Sandy GRAVEL (ALLUVIUM) Brown and black, moist to wet, medium dense to dense. Fine to medium, subrounded gravel. Trace fine to coarse grained sand.																16,17,15 N=32	SPT
8					H		(GP)																
9					J																	4,5,6 N=11	SPT
9.50	-2.16					Silty CLAY (ALLUVIUM)																	
10							(CH)																

REMARKS Kgwu - Wundaru Granodiorite;

Sample failed along existing defect surface.

Rock roller bit used 21.60m to 22.00m.

LOGGED BY
MS

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No BH173
SHEET 2 of 3
REFERENCE No 12114

PROJECT Mackay Ring Road Geotechnical Investigation - Stage 1
LOCATION Fursden Creek Overflow Bridge Pier 1: CH: 8710m; COORDINATES 721432.6 E; 7661030.2 N
PROJECT No FG6184 SURFACE R.L. 7.34m PLUNGE _____ DATE STARTED 20/10/14 GRID DATUM GDA 94 /MGA Zone 55
JOB No _____ HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/10/14 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	-2.66													
11					K	Silty CLAY (ALLUVIUM) (Cont'd) Brown, yellow and pale grey, moist, very stiff. High plasticity.	(CH)						3,7,9 N=16	SPT
12					L								6,10,12 N=22	SPT
13					M								5,9,11 N=20	SPT
14					N								6,10,13 N=23	SPT
15					P								6,13,12 N=25	SPT
16					Q								9,13,15 N=28	SPT
17	-8.16				R	Silty Sandy CLAY (RESIDUAL) Pale brown and pale grey, moist, hard. Medium plasticity.	(CI)						9,15,20 N=35	SPT
18	-9.16				S	GRANODIORITE (Kgwu) XW: Recovered as grey-brown, moist to dry, dense to very dense Clayey SAND. Fine to medium grained sand. Clay content decreases with depth.							11,19,26 N=45	SPT
19					T								19,27,30/110	SPT
20					U	19.00m: Becoming Silty SAND.							30/90	SPT

REMARKS Kgwu - Wundaru Granodiorite;
Sample failed along existing defect surface.
Rock roller bit used 21.60m to 22.00m.

LOGGED BY
MS

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No **BH173**
SHEET **3** of **3**
REFERENCE No **12114**

PROJECT Mackay Ring Road Geotechnical Investigation - Stage 1
LOCATION Fursden Creek Overflow Bridge Pier 1; CH: 8710m; COORDINATES 721432.6 E; 7661030.2 N
PROJECT No FG6184 SURFACE R.L. 7.34m PLUNGE _____ DATE STARTED 20/10/14 GRID DATUM GDA 94 /MGA Zone 55
JOB No _____ HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/10/14 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
20	-12.66				V	GRANODIORITE (Kgwu) XW: (Cont'd)	+					30/120	SPT
21					W		+	XW				30/100	SPT
21.60	-14.26					GRANODIORITE (Kgwu) HW: Grey, white and pink, fine to coarse grained, very low strength. 22.00m: Becoming MW with high strength.	+	HW				21.60m-22.00m: Rock Roller bit used.	
22	-14.86		(90)			MICRODIORITE (Kgwu) SW: Black, fine to medium grained, massive, high to very high strength. Some thin calcite veins throughout. Defects: - Js; 5°-15° (2/m); Pl/Ro, OP, some CA Ct; - Js; 30° (1/m); Pl/Ro, OP, some CA Ct;	+	MW				Is(50) = 2.37MPa; #	A (22.35m)
23			100				+					UCS=140MPa Is(50) = 6.53MPa Is(50) = 8.56MPa	A (23.40m) A (23.45m)
24			(85)				+	SW				Is(50) = 3.47MPa; # Is(50) = 1.92MPa	D (23.90m) A (23.95m)
25			100				+					Is(50) = 5.44MPa	A (24.80m)
25.80	-18.46						+					Is(50) = 10.46MPa Is(50) = 12.08MPa	D (25.59m) A (25.62m)
26			100			GRANODIORITE (Kgwu) SW: Pink, white and grey, fine to coarse grained, massive, medium to high strength.	+	SW					
26.90	-19.56		(57)				+	HW				26.00m-26.15m: HW zone.	
27						MICRODIORITE (Kgwu) SW: Black, fine to medium grained, massive, very high strength. Defects: - Js; 20° (1/m); Pl/Ro, OP, Cn; - Js; 30°-40° (2/m); Pl/Ro, OP, Cn;	+	MW				26.15m-26.45m: MW Microdiorite, medium strength.	
27.58	-20.24		100				+	SW				Is(50) = 0.52MPa; #	D (26.65m)
28							+					Is(50) = 7.21MPa	D (27.10m)
29							+						
30							+						

REMARKS Kgwu - Wundaru Granodiorite;

Sample failed along existing defect surface.

Rock roller bit used 21.60m to 22.00m.

LOGGED BY
MS


CORE PHOTO LOG

DEPARTMENT OF TRANSPORT & MAIN ROADS
Geotechnical Branch
35 Butterfield Street, HERSTON Qld 4006
Phone 07 3066 3336



Department of
Transport and Main Roads

Project Name	Mackay – Ring Road		
Project No	FG6184	Date	21/10/14
Borehole No	BH173	TMR H No	12114
Location	Fursden Creek Overflow Bridge	Start Depth (m)	22.0
Detail	Pier 1	Finish Depth (m)	27.58
Chainage	8710m	Submitted By	J. Lopez
Remarks			



SCALE 1:5