COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department and author as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence, prepared by Arup". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

This log has been contributed to the Queensland Geotechnical Database with the permission of Arup.

ARL	JP	BOREHOLE RECORD							30)4			SHEET 1 OF 3		
CLIENT	DMR						OLE GGF	D BY	Y		MA	A.J			
PROJECT		CH MOTO	CH MOTORWAY UPGRADE - WACOL TO DARRA						LOGGED BY - CHECKED BY DRILLED DATE				••		
												-Apr			
CONTRACTOR DRILL MODEL		rratest dson 3000)		ANGLE Vertical BEARING -	GROUND LEVE LOCATION			:L			.14m 'E 151280 N			
DRILLER	Te	rratest			HOLE DIAMETER 100mm ()			ELEVATION DATUM					an Height Datum		
	T					CO	ORDI	NATE	SYS	TEM	Loc	;al Gi	rid		
DRILLING		STRA	TA		MATERIAL DESCRIPTION			CONDITION					OBSERVATION		
			7			UI CONSIST				TENCY		\exists			
SAMPLE, TEST,	R.L.	DEPTH	SYMBOL	Q.	SOIL TYPE	WATER / MOISTURE		CON	NOIO	TEINC	, 1	_	SOIL ORIGIN		
BIT, SUPPORT, ETC.			JP S	LEGEND	Plasticity / Grain Size, Colour, Minor Components	VATE	CC	HESI	IVE		NON HESI		STRUCTURE ETC.		
EIG.	m	m	GROUP			> \overline{\over	ς,	ST	TS.		₽,	, e	EIO.		
	22.99	0.15			Sandy LOAM (Vacuum excavation, no data obtained, information		70)		ĺΤ			Ħ			
	22.99	0.15	SP		assumed from surrounding exploratory holes, TP241 and TP242). Clayey SAND (SP) loose to medium dense, medium to coarse grained,	1									
		İ			(Vacuum excavation, no data obtained, information assumed from surrounding exploratory holes, TP241 and TP242).]									
		I													
	.	<u> </u> 1			-										
		+				-									
	21.64	1.50											001:		
	21.04	† 1.50	CI CH		 Sandy CLAY (CI - CH) stiff to very stiff, red grey orange mottle, sand fime to medium grained, with medium grained sub-rounded ironstone 	1							COHES		
		†_		E	gravels.	1									
		+ 2		E	- -										
D		I		<u> </u>											
SPTLS N=17 3;5,12	20.54	2.60			Silty MUDSTONE, fine grained, extremely low strength grey red with								MUD		
0,0,12		+			 orange mottle, (Properties of a very stiff Silty CLAY (CI) with fine grained 	-							WIOD		
J	-	-3			_ sand). 	1									
SDTI S N=43		†			-	-									
		Ť				1									
		İ]									
		4													
SPTLS N=43 14;21,22	18.94	4.20		X X	Clayey SILTSTONE, fine grained, extremely low strength light grey,				Ц				MUD		
		+		× × >	- (Properties of a very stiff to hard Clayey SILT (MH), with pockets of very	-							WOD		
		+		× × × × × × × × × × × × × × × × × × ×	low strength MUDSTONE and lenes of silty sand fine grained sand).	-									
		t		× × × × × × × × × × × × × × × × × × ×	-	1									
	-	 5		× × ×	-	1									
		I		× × ×											
SPTLS N=38 10;16,22		1		× × × × × × × × × × × × × × × × × × ×		_									
10,10,22		+		× × ×	-	-									
	-	+6		× × ×	-	1									
		† _		× × × × × × × × × × × × × × × × × × ×	-	1									
	16.74	6.40			Silty MUDSTONE, fine grained, extremely low strength light grey, - (Properties of a very stiff Silty CLAY (CH)).								MUD		
		1			- (Chill)										
SPTLS N=24	16.14	7 7.00			MUDSTONE, fine grained, extremely low strength light grey, (Properties	-							MUD		
6;9,15		†			of a very stiff CLAY (CH)).	-									
		†				1									
J	15.54	7.60			Silty MUDSTONE, fine grained, extremely low strength light grey,	1							MUD		
		‡ ₈			- (Properties of a very stiff Silty CLAY (CH)).										
		"			-										
	14.74	8.40		\times	Clavey SILTSTONE fine prained extremely law strength light grow	-			Ц				MUD		
SPTLS N=47* 7;41/260		+		× × ×	Clayey SILTSTONE, fine grained, extremely low strength light grey, - (Properties of a very stift to hard Clayey SILT (MH), with sand fine	-							IVIOD		
, 30		†		× × × × ×	grained and trace charcoal ash).	-									
	-	 9		$ \times \times \rangle$	-	1									
		†		× × × × × × × × × × × × × × × × × × ×		1									
	13.64	9.50		x x x	- - Sandy MUDSTONE, fine grained, extremely low strength dark grey,]							MUD		
		<u></u>			(Properties of a very stiff to hard CLAY, with sand coarse grained and pockets of sandy CLAY).										
										\coprod		Ш			
		00mm to 2	5.45m	depth. (150mm Auger to 6m then 100mm washbore					JO	DВ				
to full de	epth.)											{	36015		

ARL	JP			В	DREHOLE RECORD	E	3H30)4	SHEET 2				
							GGED BY	MAJ	OF 3				
CLIENT PROJECT	DMR IPSWI	СН МОТС	DRWA	Y UPG	RADE - WACOL TO DARRA	СН	ECKED BY	GWE	3 pr-08				
CONTRACTOR DRILL MODEL DRILLER	End	ratest dson 3000 ratest)		ANGLE Vertical BEARING - HOLE DIAMETER 100mm ()	GF LO ELE	ROUND LEVI OCATION EVATION DATU ORDINATE SYS	23.14m 767 E 151280 N tralian Height Datum					
DRILLING		STRAT	ГА		MATERIAL DESCRIPTION		CONDITI	ON	OBSERVATION				
SAMPLE, TEST, BIT, SUPPORT, ETC.	R.L.	DEPTH m	GROUP SYMBOL	LEGEND	SOIL TYPE Plasticity / Grain Size, Colour, Minor Components	WATER / MOISTURE	CONSIS	NON COHESIVE	_ E1C.				
SPTLS N=29 6;12,17	-	- - - - 11	0		Sandy MUDSTONE, fine grained, extremely low strength dark grey, - (Properties of a very stiff to hard CLAY, with sand coarse grained and pockets of sandy CLAY). (continued) 10.60 Sandy MUDSTONE, mottle grey orange red, sand medium - grained	-	- W E 0) > 1		MUD				
SPTLS N=26 8;11,15	11.94 - - - -	- 11.20 - - - - 12		× × × × × × × × × × × × × × × × × × ×	Clayey SILTSTONE, fine grained, extremely low strength grey, - (Properties of a very stiff to hard Clayey SILT, with sand fine grained and ironstaining).				MUD				
SPTLS N=49 10;18,31	10.64	12.50 - 13		×××	Sandy MUDSTONE, fine grained, extremely low strength dark grey red mottle, (Properties of a hard Sandy CLAY, with sand fine grained and ironstaining).	-			MUD				
SPTLS N=57* 17;53/280	8.94 - - - -	- 14 - 14.20 15			Clayey SANDSTONE, medium grained, extremely low strength grey, (Properties of a very dense Clayey SAND) 14.40 Silty SANDSTONE				SNDSTN				
SPTLS N=53* 13;51/290	6.74 -	- 16 - 16.40 - 17			15.40 wih coarse quartz sand Sandy MUDSTONE, medium grained, extremely low strength grey with red orange mottle (Properties of a Sandy CLAY (CH), sand fine to medium grained, ironstaining). 16.60 Pocket of Sandy CLAY, sand medium grained, red grey orange mottle, with quartz sand.				MUD				
SPTLS N=57* 13;53/280	-	- - - - 18				-							
SPTLS N=47 13;17,30	- 4.54 - - - - -	- 18.60 - 19 - 19			MUDSTONE, XL strength, small cubic fractures, dark grey, (Properties of a hard CLAY (CH)).				MUD				
	Hole Diameter 100mm to 25.45m depth. (150mm Auger to 6m then 100mm washbore to full depth.)								_{ЈОВ} 86015				

ARL	JΓ			В	DREHOLE RECORD		3H	3(<i>J</i> 4	ŀ		OF 3
CLIENT	DMR									MAJ		
PROJECT		СН МОТО	MOTORWAY UPGRADE - WACOL TO DARRA						_	GWE		
CONTRACTOR		ratest			ANGLE Vertical		ROUNE					pr-08 3 14m
DRILL MODEL	En	dson 3000)		BEARING -		CATIC		LL	L RL 23.14m 32767 E 151280 I		
DRILLER	Tei	rratest			HOLE DIAMETER 100mm ()			ELEVATION DATUM COORDINATE SYST				ilian Height Datum Grid
	Τ											
DRILLING	STRATA			MATERIAL DESCRIPTION	CONDITION			1		OBSERVATIO		
			SYMBOL			CONSIST			STEN	TENCY		SOIL OBIOIN
SAMPLE, TEST, BIT, SUPPORT, ETC.	R.L.	DEPTH	SYN	LEGEND	SOIL TYPE Plasticity / Grain Size, Colour, Minor Components	MATER / MOISTER / COHESIVE			.	NON		SOIL ORIGIN, STRUCTURE,
			GROUP (Ĕ		S S T S T H H D D D						
	m	m	GF			-	<u>></u> ა ⊩	SI	∓ ⋝ ∎	┵	유불	MUD
	2.94	20.20			Silty MUDSTONE, very low strength (Properties of a hard Silty CLAY).				Ш			MUD
SPTLS N=61*		†				1			Ш			
17;55/270		Ī]			ш			
	-	<u> </u>				1			Ш			
		 				-						
	1.64	21.50			CITATION CANDOTONIC CONTRACTOR AND AND AND AND AND AND AND AND AND AND	-						CHIDOTH
	,	†			Clayey SANDSTONE, fine to medium grained, XL strength, XW grey,.	1						SNDSTN
	.	+ - 22]						
SPTLS N=69** 30/130s		ļ ∣			-	_			ш			
		-				-			Ш			
		+				-			ш			
		† <u> </u>			-	1			Ш			
	-0.06	23 23.20			23.00 SAND, loose, medium to coarse grained, with fine grained gravels				Ш			
SPTLS N=75* 20;30/120	-0.00	25.20			Sandy MUDSTONE, VL strength, dark grey, (Properties of a hard Sandy CLAY, sand fine grained).]			Ш			MUD
		+			- CLAT, Sand line grained).	-			Ш			
		+				-			Ш			
	-	- 24			-]			Ш			
		Į l]			ш			
		+			24.50 with sandy clay	-			Ш			
		+			24.80 becoming black	-			Ш			
SPTLS N=72* 26;30/125	-1.86 -	25 25.00						П	•			
20,007.20		1										
		-			Borehole completed at 25.45m depth	-						
		+			-	-						
	-	26			-	-						
		<u> </u>]						
		↓			-]						
		 				-		$ \ \ $				
	-	27			-	-						
		†			-	1						
		Į]		$ \ \ $				
		↓				-						
	-	- 28			_	-						
		†				1						
		<u> </u>]		$ \ \ $				
					•			$ \ \ $				
	-	- 29			_	-						
		†				-						
		†			<u> </u>	1		$ \ \ $				
		<u> </u>				1		$ \ \ $				
								Ш	Щ		Ш	
		00mm to 25	5.45m	depth. (150mm Auger to 6m then 100mm washbore					JOB		
to full de	ptn.)											86015