COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department and author as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence, prepared by Arup". This licence does not apply to logos or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

This log has been contributed to the Queensland Geotechnical Database with the permission of Arup.

													
	ARU					TEST PIT RECORD	TP	Т	P	7	•		SHEET 1
Ocotechnics								GGED BY AE					OF 1
								ATE/S			10	0.5.99	
CONTRACTOR Akuika EQUIPMENT TYPE Excavator MODEL 8 tonne Kobeko						EXCAVATION TYPE			GROUND LEVE				
						LENGTH	Lo	LOCATION				See F	gure 2
						WIDTH	-						19610 2
							-						· ·
	EXCAVATION	ļ	STRA			MATERIAL DESCRIPTION		CONDITIO					OBSERVATION
				GROUP SYMBOL	_				CON	SISTI	STENCY		
	SAMPLE, TEST,	R.L.	DEPTH) ¥	LEGEND	SOIL TYPE	WATER / MOISTURE	<u> </u>					SOIL ORIGIN,
	BIT, SUPPORT, ETC.			ਕੁ	👸	Colour, Plasticity, Grain Size, Minor Components	ATE	COI	IESIN	Æ	NC COHE	ON SIVE	STRUCTURE,
	1	AHD		Į ž	-		≥≥		. <u>t</u>			- 1	ETC.
		And	m	CH	1	Condu Cl AV Companies and any blak should		≍တၤ	<u> </u>	ᡸ	⋨⊣ѯ	209	
				L		Sandy CLAY: Orange brown and grey, high plasticity, very stiff							RESIDUAL
	ļ.] -	-	٠.	$\ \cdot\ $	-	1						
						·							
	ļ	.	[•]						
								$ \ \ $			11		
	ļ.	.	ļ]						
						·					11		
	ļ	-]				П]	
										H			
	-	-	1.00		Щ			$ \ \ $			11		
				SC	V:/:	Clayey SAND/Sandy CLAY: Light grey and light brown, dense					11		
	ļ.	-	ļ		V./.]						
				ļ.	V./.								
	ļ.		ļ		1./.				П				
			Į		V./.			$ \ \ $	11	11			
	ļ.	4			1./.		1						
					V. /.						11		
	ļ.	· ya			/./.		ļ						
		3,41			///						11		
	-		-2		1//]						
		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	_		1//	Tending towards XW Mudstone			1				
	ļ	, ·-]						
		7											
	}				///]			$\ \cdot\ $			
			2.50		Y / /	OANDOTONE O	1				11		
	-		-			SANDSTONE: Orange brown and light grey, extremely weathered	ļ		11				XW SANDSTONE
	<u></u>		2.80		02022		\vdash		₩	$\frac{1}{1}$	₩.		·
	-		-3			<u>-</u>]						
	}] -	<u> </u>				. ↓			$ \cdot $			
									$ \cdot $	$ \cdot $			
	}		-			· •	. I						
İ													
	ļ.		- ,			-	↓						
						•				$ \cdot $			4
	ŀ	j.	.				,			$ \cdot $		$\mid \mid \mid \mid$	
										$ \cdot $			
2	-	-	-4			<u>-</u>	↓ │						
Š												$ \ \ $	
3			.]						
١							1						
إ	• •		.		[]]						
ą													
51	-	i	.]						
۱													
3	ļ	↓	.]				Į	+					
,	NOTES										JOB		
Situated in a localised depression													
١	., 5			p, 00	J. J								
												11	702/2
l												• '	· Vinil In
ľ													
١										.			
ı													