

## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

MAIN ROADS DEPARTMENT

H384

Form 232L  
(P/4/66)

DRILLING REPORT

PROJECT PETRIE BIGHT EXPRESSWAY GEOTECHNICAL INVESTIGATION PROJECT No. 2-33  
 DISTRICT No. 13 SHIRE BRISBANE CITY HOLE No. 2  
 ROAD PETRIE BIGHT EXPRESSWAY JOB No. 140/E010/U02.2  
 LOCATION IVORY ST, 7' S of northern alignment, RL DATUM B.C.C.  
 and 325.5' W from western alignment of MAIN ST COLLAR -  
 TYPE AND SIZE OF DRILLING 0-1.8' Tubes; 1.8'-17.0' GROUND SURFACE 73.7  
 BXM Diamond Drilling ROCK SURFACE -  
 BOTTOM OF HOLE 56.7  
 DATE DRILLED 2nd October, 1967. WATER TABLE -

DEPTH 1" = 5'	% CORE REC.	DIAGRAM	STRATA	DESCRIPTION OF SOIL ROCK	SAMPLE	
					No.	TYPE
0.5			PAVEMENT			
1.7			DECOMPOSED TUFF	dark grey to black mainly soft - partly carbonaceous	A	Tube
1.9					B	Tube
5.5	100		HIGHLY WEATHERED PHYLLITE	2.5'-3.5' unconformity breccia  3.5'-17.0' white to green, mainly soft, flaky numerous quartz veins follow very numerous cleavages - dip of cleavage var- iable from 15°-40°		
8.0	100					
12.5	97					
17.0	68				17.0	
				END OF HOLE		

DRILLER C.W. D.R. R.T. PLANT MRD GEMCO 9467

REMARKS

DATE 4/10/67 G.H. Shipway GEOLOGIST APPROVED [Signature] DATE 20/10/67