## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



TMR JAN 15.GLB Log A\_ENGINEERING BOREHOLE LOG W LITHOLOGY FG6184 - BOREHOLES.GPJ <<DrawingFile>> Datgel CPT Tool gINt Add-In 04/03/2015 10:51

## ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

 BOREHOLE No
 BH129

 SHEET
 1 of 2

 REFERENCE No
 12075

				Geotechnical Investigation - Stage 1								— — — · 9 N
	<u>FG61</u>	184		SURFACE R.L. <u>9.82m</u> PLUNGE HEIGHT DATUM <u>AHD</u> BEARING			DA	ATE S		/ <u>10/14</u>	GRID DATUM GDA 94 /MGA	Zone 5
R.L. (m)	AUGER CASING WASH BORING	RQD ()%	SAMPLE	MATERIAL DESCRIPTION	гітногоду	SC EATHERING	INTA STREM		DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA  AND  TEST RESULTS	SAMPLES TESTS
0 9.82	₹0≥	REC %	<i>l</i> S	Sandy SILT (TOPSOIL) Brown, moist, soft.	7/1/	(ML)				5		- S/ - S/
9.32 - - - - - - - - - - - - - - - - - - -			Α	Low plasticity.  Silty SAND (ALLUVIUM)  Brown, moist, mainly loose to medium dense.  Fine grained.							2,3,4 N=7	SPT :
			В								3,4,3 N=7	SPT -
-3 - - - - - -			С	3.00m: Becoming fine to medium grained.		(SM)					3,3,3 N=6	SPT -
			D	4.00m: Becoming medium dense.							3,6,5 N=11	SPT -
-5 - - - - - 4 22			Е								3,6,7 N=13	SPT =
-5.50 4.32 			F	Gravelly Silty SAND (ALLUVIUM) Brown, moist, dense. Fine to medium grained sand. Medium, subrounded gravel.		(SM)					3,15,17 N=32	SPT -
			G	Sandy GRAVEL (ALLUVIUM) Brown and black, moist, medium dense to very dense. Fine to medium, subrounded gravel. Fine to coarse grained sand.							30/140	SPT _
			Н			(GW)					24,23,20 N=43	SPT -
- -9  - -  -9.50 0.32			J	Silty Gravelly SAND (ALLUVIUM)							4,9,8 N=17	SPT -
REMARK	s			Brown, moist, medium dense. Fine to coarse grained sand. Medium	# 	(SM)					LOGGED BY MS	- - -



TMR JAN 15.GLB Log A\_ENGINEERING BOREHOLE LOG W LITHOLOGY FG6184 - BOREHOLES.GPJ <<DrawingFile>> Datgel CPT Tool glNt Add-In 04/03/2015 10:51

## ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No \_\_BH129\_\_\_

SHEET \_\_2\_ of \_2\_\_

REFERENCE No \_\_12075\_\_\_

	JECT					Geotechnical Investigation - Stage 1								COORDINATES 721373.9 E; 7660790.9 N
														10/14 GRID DATUM GDA 94 /MGA Zone 5
JOB No HEIGHT DATUM AHD BEARING DATE COMPLETED 9/10/14 DRILLER Saxon Drilling										0/14 DRILLER <u>Saxon Drilling</u>				
DEPTH (m)	R.L. (m)	AÚGER SASING WASH BORING		RQD ( )%	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY		WEATHERING	INTACT STRENGTH	D SF	EFECT PACING (mm)	EW SPAPHIC I OG	GRAPHIC LOG AND TEST RESULTS  RAMPLES SAMPLES
10.60	-0.78					gravel. Silty Gravelly SAND (ALLUVIUM) (Cont'd)			SM)					7,11,14 N=25
- - - 11 - - - - - - - - - -	-2.08				L	Sandy GRAVEL (ALLUVIUM) Brown and black, moist, medium dense. Fine to medium gravel. Fine to coarse grained sand.		((	€W)					11,14,9 N=23
- 12 - - - - - -					M	Sandy Silty CLAY (RESIDUAL) Brown and yellow mottled grey, moist, stiff to very stiff. Medium to high plasticity.								4,9,18 N=27
- 13 - - - - - -					Z				CI- CH)					6,7,8 N=15
14      					Р	14.00m: Becoming Silty CLAY. High plasticity.								6,7,10 N=17
- 15 - - - - - <sub>15.45</sub>	-5.63				Q									5,6,8 N=14 SPT
						Borehole terminated at 15.45m								
	REMARK	S									L: 			LOGGED BY
								_	- —				- —	MS