## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



## **ENGINEERING BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/6-2010

	ROJECT <u>EIGHT MILE CREEK BRIDGE FOUNDATION INVESTIGATION</u> COATION Abutment A - RHS (Ch.83866.225)  COORDINATES 2											
LOCATION         Abutment A - RHS (Ch. 83866.225)         COORD           PROJECT No         FG5934         SURFACE R.L.         7.44m         PLUNGE         DATE STARTED 16/8/11												
JOB 1						HEIGHT DATUM <u>AHD</u> BEARING						
DEPTH (m)	R.L. (m)	IR VG T BORING			SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA  AND  TEST RESULTS  ADDITIONAL DATA  SS  WE ST  ST  ST  ST  ST  ST  ST  ST  ST  ST
0	7.44	₹ O		REC %	0)	Clayey SILT (RESIDUAL)				<u> </u>	0	
1	5.24				Α	Grey to yellow brown, moist, firm.  Medium plasticity; some tree roots.		(ML)				Upper area based on Driller's log only  2,2,3 N=5
	5.24					SILTSTONE						20/20
- - - - -3 -					В	Fine grained, thinly laminated, sedimentary rock XW: Generally exhibits the engineering properties of yellow brown to grey, moist, hard clayey silt.  Low plasticity; some HW rock kernels.		xw				30/80mm N>50
F	3.84			(31)	С	SANDSTONE			: : : : : : <u>-</u>			HB N>50 SPT
3 - 3				100 (25)		Fine grained, mainly massive, poorly cemented sedimentary rock  MW: Grey to slightly brown, fine grained, massive, medium to high strength.  Defects: - Lamination partings @ 15-25° (8/m) - Joints @ 30-45° (5/m) - Joints @ 60-70° (2/m)  Defect surfaces are generally planar, rough, open, iron stained.						Is(50) = 0.79MPa o Is(50) = 1.02MPa o
- - - - 6 - -				100		Becoming grey to dark brown, thin siltstone interbeds.		MW				CLy seam, 30°, 10mm CLy seam, 15°, 60mm
- 6 7 - 7 8 9				(6)								— CLy seam, 40°, 10mm
-8				100								Is(50) = 1.42MPa x
- - -				(16)				HW				Is(50) = 0.56MPa o
-9 -				(20)		Becoming black to dark grey, fine to medium grained.		MW				
- - - - 10						Very thin siltstone interbeds. Numerous closely spaced lamination partings (35°)						
	REMARKS Failures may have been taken place along pre-existing defect plains								LOGGED BY			
									MS / AD			



## **ENGINEERING BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No	BH02
SHEET	_2_ of _2_
REFERENCE No	

PROJECT E	EIGHT MILE CREEK BRIDGE FOUNDATION INVESTIGATION											
LOCATION A	Abutment A - RHS (Ch.83866.225) COORDINATES										. <u>8 E; 7380636</u> .	3 N
PROJECT No F	G5934		SURFACE R.L 7.44m PLUNGE			DATE S	TARTED _	16/8/	<u>11_</u> GR	RID DATUM	MGA94 Zone	56
JOB No _2	258/10E/1		HEIGHT DATUM <u>AHD</u> BEARING			DATE COM	IPLETED _	<u>11</u>	DRILLER	Saxon Drilling	Pty Ltd_	
R.L. (m) HLA W W W W W W W W W W W W W W W W W W W	RQD ( ) % ( ) % ( ) % ( ) CORE ( ) CORE	SAMPLE	MATERIAL DESCRIPTION	ПТНОГОСУ	SC /EATHERING	INTACT STRENGTH  ###################################	DEFECT SPACING (mm)	GRAPHIC LOG		DDITIONAL I AND TEST RESU		SAMPLES
10 -2.57 ₹Ů	S ≥ O REC %	Ś	CANDSTONE	=	jš ≥	11111		ō	Piezocone	observation w	ell tip at 10.0m	S E
2.672 CAREKE BHI TO B-NB GED C ACTION BINE CAT TO B-NB GED C ACT TO B-NB GED C ACTION BINE CAT T			SANDSTONE MW: (Cont'd) Borehole terminated at 10.1m						Piezocone	cobservation w	ell tip at 10.0m	
THE TOTAL THE TO	ailures may h	ave	peen taken place along pre-existing defect plains								OGGED BY	
_									_	MS / AD		

Project: **EIGHT MILE CREEK BRIDGE (ABUTMENT A)** 

Borehole No: BH2
Start Depth: 3.60m
Finish Depth: 10.10m
Project No: FG5934

H No:



