

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.





Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	<u>BH170</u>
SHEET	<u>1</u> of <u>3</u>
REFERENCE No	<u>12111</u>

PROJECT Mackay Ring Road Geotechnical Investigation - Stage 1
LOCATION Fursden Creek Overflow Bridge Abutment A; CH: 8691m; COORDINATES 721415.3 E; 7661013.3 N
PROJECT No FG6184 SURFACE R.L. 7.32m PLUNGE _____ DATE STARTED 21/10/14 GRID DATUM GDA 94 /MGA Zone 55
JOB No _____ HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 22/10/14 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH								DEFECT SPACING (mm)					GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS		
									EH	VH	H	M	J	VL	EL	EC	VC	WC	W	WW	VW				EW	
0	7.32					Silty CLAY (ALLUVIUM) Brown, dry to moist, stiff. High plasticity.																		3,4,5 N=9	SPT	
1					A				(CH)																	
1.60	5.72					SAND (ALLUVIUM) Pale brown, moist, loose to medium dense. Fine to medium grained sand. Trace fine to medium gravel.																		2,3,3 N=6	SPT	
2					B				(SP)																	
3					C																					
4					D																					
5					E																					
6						F														6,7,8 N=15	SPT					
7					G																					
7.60	-0.28					Gravelly SAND (ALLUVIUM) Brown, moist to wet, medium dense.																4,4,5 N=9	SPT			
8					H				(SW)																	
9.00	-1.68					Silty CLAY (ALLUVIUM) Pale grey and brown, moist, stiff. High plasticity.																18,12,3 N=15	SPT			
9					J				(CH)																	
10.10	-2.68																				3,5,7 N=12	SPT				

REMARKS Kgwu - Wundaru Granodiorite;
Sample failed along existing defect surface.
Rock Roller bit used 18.27m to 22.00m.

LOGGED BY
ME



ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	BH170
SHEET	2 of 3
REFERENCE No	12111

PROJECT Mackay Ring Road Geotechnical Investigation - Stage 1

LOCATION Fursden Creek Overflow Bridge Abutment A; CH: 8691m; COORDINATES 721415.3 E; 7661013.3 N

PROJECT No FG6184 SURFACE R.L. 7.32m PLUNGE _____ DATE STARTED 21/10/14 GRID DATUM GDA 94 /MGA Zone 56

JOB No _____ HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 22/10/14 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	WEATHERING										DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS			
								USC	EH	VH	H	M	J	VL	EL	EC	VC					C	W	VW
10	-2.68				K	Silty CLAY (ALLUVIUM) (Cont'd) Becoming very stiff.	(CH)																3,7,9 N=16	SPT
11					L																		5,10,12 N=22	SPT
12					M	12.00m: Becoming hard.																	6,13,20 N=33	SPT
12.80	-5.48				N	Sandy Silty CLAY (RESIDUAL) Pale grey, brown and black, moist, very stiff to hard. High plasticity.	(CH)																8,12,16 N=28	SPT
13					P																		7,10,14 N=24	SPT
14					Q																		5,12,20 N=32	SPT
15					R																		7,10,14 N=24	SPT
16					S	MICRODIORITE (Kgwu) XW: Recovered as grey, moist, hard Gravelly Silty CLAY.	XW																11,12,20 N=32	SPT
17					T																		27,30/115	SPT
18					U																		18.27m-22.09m: Rock Roller bit used.	SPT
19																								
20	-9.48																							
21																								
22	-12.68																							

REMARKS Kgwu - Wundaru Granodiorite;

Sample failed along existing defect surface.

Rock Roller bit used 18.27m to 22.00m.

LOGGED BY
ME

**ENGINEERING
BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No BH170
SHEET 3 of 3
REFERENCE No 12111

PROJECT Mackay Ring Road Geotechnical Investigation - Stage 1
LOCATION Fursden Creek Overflow Bridge Abutment A; CH: 8691m; COORDINATES 721415.3 E; 7661013.3 N
PROJECT No FG6184 SURFACE R.L. 7.32m PLUNGE DATE STARTED 21/10/14 GRID DATUM GDA 94 /MGA Zone 55
JOB No HEIGHT DATUM AHD BEARING DATE COMPLETED 22/10/14 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING											DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
									EH	VH	H	M	J	VL	EL	EC	VC	W	WW				
20	-12.68				V	MICRODIORITE (Kgwu) HW: Grey, fine grained, very low strength.															30/120	SPT	
21					W		HW													18.27m-22.09m: Rock Roller bit used.	30/100	SPT	
22	-14.77				X	MICRODIORITE (Kgwu) SW: Grey, fine to medium grained, massive, very high strength. Defects: - Js; 0°-30° (3/m); Pl/Sm, TI-CD, some Cly; - Js; 30°-60° (3/m); Pl/Sm, TI-CD, some Cly; - Js; 60°-90° (1/m); Pl/Sm, TI-CD, some Cly;														22.25m-22.35m: Core Loss 22.45m-22.46m: Clay seam.	30/90	SPT	
23			(0) 71				SW													Is(50) = 1.02MPa; # A (22.85m) Is(50) = 1.46MPa; # D (22.90m)			
24			100 (10)				SW													Is(50) = 1.23MPa; # D (23.20m) Is(50) = 4.33MPa A (23.28m)			
25			100 (70)				HW													23.80m-23.81m: Clay seam. 23.95m-24.25m: CS (5x); 10mm. 24.35m-24.55m: MW Granodiorite			
26							SW													24.85m-25.10m: HW zone, CA; Is(50) = 2.44MPa D (25.30m) Is(50) = 4.10MPa; # A (25.36m)			
26.48	-19.16		100			Borehole terminated at 26.48m.														Is(50) = 7.39MPa D (26.45m)			
27																							
28																							
29																							
30																							

REMARKS Kgwu - Wundaru Granodiorite;
 # Sample failed along existing defect surface.
 Rock Roller bit used 18.27m to 22.00m.

LOGGED BY
ME


CORE PHOTO LOG

DEPARTMENT OF TRANSPORT & MAIN ROADS
 Geotechnical Branch
 35 Butterfield Street, HERSTON Qld 4006
 Phone 07 3066 3336



Department of
Transport and Main Roads

Project Name	Mackay – Ring Road		
Project No	FG6184	Date	22/10/14
Borehole No	BH170	TMR H No	12111
Location	Fursden Creek Overflow Bridge	Start Depth (m)	22.0
Detail	Abutment A	Finish Depth (m)	26.48
Chainage	8691m	Submitted By	M.Ensor
Remarks			



SCALE 1:5